

AC axial fan

sickle-shaped blades (S series)
for forced ventilation

W2D155-EA08-01 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	W2D155-EA08-01			
Motor	M2D068-BC			
Phase		3~	3~	3~
Nominal voltage	VAC	400	400	480
Wiring		Y	Y	Y
Frequency	Hz	50	60	60
Method of obtaining data		ce	ce	ce
Valid for approval/standard		CE	CE	CE
Speed (rpm)	min ⁻¹	2600	2870	3060
Power consumption	W	36	42	51
Current draw	A	0.09	0.08	0.1
Min. ambient temperature	°C	-25	-25	-25
Max. ambient temperature	°C	80	80	80
Starting current	A	0.2	0.2	0.22

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



AC axial fan

sickle-shaped blades (S series)
for forced ventilation

Technical description


Weight	3.8 kg
Size	155 mm
Motor size	68
Rotor surface	Painted black
Terminal box material	Die-cast aluminum
Impeller material	Sheet steel, painted black
Housing material	Die-cast aluminum, painted black
Guard grille material	Die-cast aluminum
Number of blades	5
Airflow direction	A
Direction of rotation	Counterclockwise, viewed toward rotor
Degree of protection	IP55
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	H1+
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	< 0.75 mA
With cable	Lateral
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1, motor does not have factory-installed overheating protection; CE
Approval	UL 1004-1; CSA C22.2 No. 100



AC axial fan

sickle-shaped blades (S series)
for forced ventilation

Product drawing




- | | |
|---|------------------------------|
| 1 | Direction of air flow "A" |
| 2 | Screw plug M20 x 1.5 |
| 3 | Tightening torque 1.6±0.2 Nm |

AC axial fan

sickle-shaped blades (S series)
for forced ventilation

Connection diagram



Change of rotation direction by reversing two phases


	Three-phase motor
Y	Star connection
1	Counterclockwise operation
L1	= V1 = blue
L2	= U1 = black
L3	= W1 = brown
2	Clockwise operation
L1	= U1 = black
L2	= V1 = blue
L3	= W1 = brown
PE	green/yellow



AC axial fan

sickle-shaped blades (S series)
for forced ventilation

Curves: Air performance 50 Hz



Measurement: LU-111555-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _e	I	q _v	q _v	p _{fs}
		V	Hz	min ⁻¹	W	A	m³/h	cfm	in. wg
1	Y	400	50	2600	36	0.09	135	80	0.00

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow

