

# AC axial compact fan

sickled blades (S series), single inlet

W2D200-HH04-11 ebmpapst Datasheet  
sales@fansco.com  
www.fansco.com

Nominal data

|                               |                   |            |            |
|-------------------------------|-------------------|------------|------------|
| Type                          | W2D200-HH04-11    |            |            |
| Motor                         | M2D068-BC         |            |            |
| Phase                         |                   | 3~         | 3~         |
| Nominal voltage               | VAC               | 230        | 230        |
| Nominal voltage range         | VAC               | 190 .. 240 | 190 .. 240 |
| Connection                    |                   | Δ          | Δ          |
| Frequency                     | Hz                | 50         | 60         |
| Type of data definition       |                   | fa         | fa         |
| Valid for approval / standard |                   | CE         | CE         |
| Speed (rpm)                   | min <sup>-1</sup> | 2500       | 2650       |
| Power input                   | W                 | 52         | 62         |
| Current draw                  | A                 | 0.19       | 0.19       |
| Min. ambient temperature      | °C                | -25        | -25        |
| Max. ambient temperature      | °C                | 80         | 80         |
| Starting current              | A                 | 0.23       | 0.22       |

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit  
Subject to alterations



# AC axial compact fan

sickled blades (S series), single inlet

## Technical features


|                                                                    |                                                                              |
|--------------------------------------------------------------------|------------------------------------------------------------------------------|
| Mass                                                               | 2.0 kg                                                                       |
| Size                                                               | 200 mm                                                                       |
| Surface of rotor                                                   | Coated in black                                                              |
| Material of blades                                                 | Sheet steel, coated in black                                                 |
| Material of wall ring                                              | Die-cast aluminium                                                           |
| Number of blades                                                   | 9                                                                            |
| Direction of air flow                                              | "V"                                                                          |
| Direction of rotation                                              | Counter-clockwise, seen on rotor                                             |
| Type of protection                                                 | IP 44; Depending on installation and position                                |
| Insulation class                                                   | "F"                                                                          |
| Humidity (F)/environmental protection class (H)                    | F2-2                                                                         |
| Max. permissible ambient motor temp. (transp./ storage)            | + 80 °C                                                                      |
| Min. permissible ambient motor temp. (transp./storage)             | - 40 °C                                                                      |
| Mounting position                                                  | Any                                                                          |
| Condensate discharge holes                                         | None                                                                         |
| Operation mode                                                     | S1                                                                           |
| Motor bearing                                                      | Ball bearing                                                                 |
| Touch current acc. IEC 60990 (measuring network Fig. 4, TN system) | < 0.75 mA                                                                    |
| Cable exit                                                         | Axial                                                                        |
| Protection class                                                   | I (if protective earth is connected by customer)                             |
| Product conforming to standard                                     | EN 60335-1, motor does not have factory-installed overheating protection; CE |
| Approval                                                           | CSA C22.2 No.100; UL 1004-1                                                  |



## AC axial compact fan


sickled blades (S series), single inlet

## Product drawing



|     |                                                                      |
|-----|----------------------------------------------------------------------|
| 1   | Direction of air flow "V"                                            |
| 2   | Connection line silicone 4G 1 mm <sup>2</sup> , 4x lead tips crimped |
| 2.1 | green/yellow                                                         |
| 2.2 | blue                                                                 |
| 2.3 | brown                                                                |
| 2.4 | black                                                                |

Connection screen




Note: Change direction of rotation by reversing two phases

|    |                  |    |                |    |             |
|----|------------------|----|----------------|----|-------------|
| Δ  | Delta connection | L1 | = U1 = black   | L2 | = V1 = blue |
| L3 | = W1 = brown     | PE | green / yellow |    |             |



Charts: Air flow 50 Hz



Measurement: LU-21426-1

Air performance measured as per ISO 5801  
Installation category A. For detailed  
information on the measuring set-up, please  
contact ebm-papst. Suction-side noise  
levels: L<sub>wA</sub> measured as per ISO 13347 /  
L<sub>pA</sub> measured with 1m distance to fan axis.  
The values given are valid under the  
measuring conditions mentioned above and  
may vary according to the actual installation  
situation. With any deviation from the  
standard set-up, the specific values have to  
be checked and reviewed with the unit  
installed.


Measured values

|   | U   | f  | n                 | P <sub>e</sub> | I    | q <sub>V</sub> | p <sub>fs</sub> | q <sub>V</sub> | p <sub>fs</sub>    |
|---|-----|----|-------------------|----------------|------|----------------|-----------------|----------------|--------------------|
|   | V   | Hz | min <sup>-1</sup> | W              | A    | m³/h           | Pa              | cfm            | inH <sub>2</sub> O |
| 1 | 400 | 50 | 2500              | 52             | 0.11 | 900            | 0               | 530            | 0.00               |
| 2 | 400 | 50 | 2450              | 56             | 0.11 | 820            | 25              | 485            | 0.10               |
| 3 | 400 | 50 | 2400              | 58             | 0.11 | 725            | 50              | 425            | 0.20               |
| 4 | 400 | 50 | 2350              | 61             | 0.11 | 575            | 70              | 340            | 0.28               |

U = Supply voltage · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power input · I = Current draw · q<sub>V</sub> = Air flow · p<sub>fs</sub> = Pressure increase



Charts: Air flow 60 Hz



Measurement: LU-21427-1

Air performance measured as per ISO 5801  
Installation category A. For detailed  
information on the measuring set-up, please  
contact ebm-papst. Suction-side noise  
levels: LwA measured as per ISO 13347 /  
LpA measured with 1m distance to fan axis.  
The values given are valid under the  
measuring conditions mentioned above and  
may vary according to the actual installation  
situation. With any deviation from the  
standard set-up, the specific values have to  
be checked and reviewed with the unit  
installed.

Measured values

|   | U   | f  | n                 | P <sub>e</sub> | I    | q <sub>v</sub>    | p <sub>fs</sub> | q <sub>v</sub> | p <sub>fs</sub>    |
|---|-----|----|-------------------|----------------|------|-------------------|-----------------|----------------|--------------------|
|   | V   | Hz | min <sup>-1</sup> | W              | A    | m <sup>3</sup> /h | Pa              | cfm            | inH <sub>2</sub> O |
| 1 | 400 | 60 | 2650              | 62             | 0.11 | 950               | 0               | 560            | 0.00               |
| 2 | 400 | 60 | 2585              | 66             | 0.11 | 880               | 25              | 515            | 0.10               |
| 3 | 400 | 60 | 2505              | 70             | 0.11 | 780               | 50              | 460            | 0.20               |
| 4 | 400 | 60 | 2410              | 73             | 0.12 | 585               | 75              | 345            | 0.30               |

U = Supply voltage · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power input · I = Current draw · q<sub>v</sub> = Air flow · p<sub>fs</sub> = Pressure increase

