

# AC axial fan

sickle-shaped blades (S series)

Fan housing with guard grille

W2D300-CQ08-46 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

## Nominal data

|                             |                   |      |      |
|-----------------------------|-------------------|------|------|
| Type                        | W2D300-CQ08-46    |      |      |
| Motor                       | M2D074-EI         |      |      |
| Phase                       |                   | 3~   | 3~   |
| Nominal voltage             | VAC               | 480  | 480  |
| Frequency                   | Hz                | 50   | 60   |
| Method of obtaining data    |                   | fa   | fa   |
| Valid for approval/standard |                   | CE   | CE   |
| Speed (rpm)                 | min <sup>-1</sup> | 2750 | 3100 |
| Power consumption           | W                 | 270  | 400  |
| Current draw                | A                 | 0.47 | 0.56 |
| Max. back pressure          | Pa                | 265  | 300  |
| Max. back pressure          | in. wg            | 1.06 | 1.2  |
| Max. ambient temperature    | °C                | 70   | 50   |
| Starting current            | A                 | 2    | 1.9  |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment  
Subject to change



# AC axial fan

sickle-shaped blades (S series)

Fan housing with guard grille

## Technical description

|                                                                            |                                                                          |
|----------------------------------------------------------------------------|--------------------------------------------------------------------------|
| Weight                                                                     | 5.92 kg                                                                  |
| Size                                                                       | 300 mm                                                                   |
| Motor size                                                                 | 74                                                                       |
| Rotor surface                                                              | Painted black                                                            |
| Blade material                                                             | Sheet steel, painted black                                               |
| Fan housing material                                                       | Sheet steel, galvanized and coated with black plastic (RAL 9005)         |
| Guard grille material                                                      | Steel, coated with black plastic (RAL 9005)                              |
| Number of blades                                                           | 5                                                                        |
| Airflow direction                                                          | V                                                                        |
| Direction of rotation                                                      | Counterclockwise, viewed toward rotor                                    |
| Degree of protection                                                       | IP44; installation- and position-dependent as per EN 60034-5             |
| Insulation class                                                           | "F"                                                                      |
| Moisture (F) / Environmental (H) protection class                          | F2-2; H1+                                                                |
| Max. permitted ambient temp. for motor (transport/storage)                 | + 80 °C                                                                  |
| Min. permitted ambient temp. for motor (transport/storage)                 | - 40 °C                                                                  |
| Installation position                                                      | Shaft horizontal or rotor on bottom; rotor on top on request             |
| Condensation drainage holes                                                | On rotor side                                                            |
| Mode                                                                       | S1                                                                       |
| Motor bearing                                                              | Ball bearing                                                             |
| Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system) | < 0.75 mA                                                                |
| With cable                                                                 | Variable                                                                 |
| Protection class                                                           | I (with customer connection of protective earth)                         |
| Conformity with standards                                                  | EN 60335-1, motor does not have factory-installed overheating protection |
| Approval                                                                   | CCC                                                                      |




# AC axial fan

sickle-shaped blades (S series)

Fan housing with guard grille

## Product drawing




1 Cable silicone 4x 0.5 mm<sup>2</sup>, 4x crimped splices

2 Direction of air flow "V"

# AC axial fan

sickle-shaped blades (S series)  
Fan housing with guard grille

## Connection diagram



Change of rotation direction by reversing two phases


|    |                            |
|----|----------------------------|
|    | Three-phase motor          |
| Y  | Star connection            |
| 1  | Counterclockwise operation |
| L1 | = V1 = blue                |
| L2 | = U1 = black               |
| L3 | = W1 = brown               |
| 2  | Clockwise operation        |
| L1 | = U1 = black               |
| L2 | = V1 = blue                |
| L3 | = W1 = brown               |



# AC axial fan

sickle-shaped blades (S series)  
Fan housing with guard grille

## Curves: Air performance 50 Hz



Measurement: LU-49327-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

|   | U   | f  | n                 | P <sub>e</sub> | I    | q <sub>v</sub> | q <sub>v</sub> | P <sub>fs</sub> |
|---|-----|----|-------------------|----------------|------|----------------|----------------|-----------------|
|   | V   | Hz | min <sup>-1</sup> | W              | A    | m³/h           | cfm            | in. wg          |
| 1 | 480 | 50 | 2750              | 270            | 0.47 | 3175           | 1870           | 0.00            |


U = Voltage · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power consumption · I = Current draw · q<sub>v</sub> = Air flow



AC axial fan

sickle-shaped blades (S series)  
Fan housing with guard grille

Curves: Air performance 60 Hz



Measurement: LU-49328-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

|   | U   | f  | n                 | P <sub>e</sub> | I    | q <sub>v</sub>    | q <sub>v</sub> | P <sub>fs</sub> |
|---|-----|----|-------------------|----------------|------|-------------------|----------------|-----------------|
|   | V   | Hz | min <sup>-1</sup> | W              | A    | m <sup>3</sup> /h | cfm            | in. wg          |
| 1 | 480 | 60 | 3100              | 400            | 0.56 | 3575              | 2105           | 0.00            |

U = Voltage · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power consumption · I = Current draw · q<sub>v</sub> = Air flow

