

W2E143-AB09-01/F01 ebmpapst Datasheet  
sales@fansco.com  
www.fansco.com

**Nominal data**

|                             |                    |         |         |
|-----------------------------|--------------------|---------|---------|
| Type                        | W2E143-AB09-01/F01 |         |         |
| Motor                       | M2E052-BF          |         |         |
| Phase                       |                    | 1~      | 1~      |
| Nominal voltage             | VAC                | 230     | 230     |
| Frequency                   | Hz                 | 50      | 60      |
| Method of obtaining data    |                    | fa      | fa      |
| Valid for approval/standard |                    | CCC     | CCC;UL  |
| Speed (rpm)                 | min <sup>-1</sup>  | 2800    | 3300    |
| Power consumption           | W                  | 24      | 30      |
| Current draw                | A                  | 0.12    |         |
| Capacitor                   | μF                 | 0.75    | 0.75    |
| Capacitor voltage           | VDB                | 400     | 400     |
| Capacitor standard          |                    | P0 (CE) | P0 (CE) |
| Min. ambient temperature    | °C                 | -25     | -25     |
| Max. ambient temperature    | °C                 | 60      | 75      |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment  
Subject to change




## Technical description

|                                                                            |                                                       |
|----------------------------------------------------------------------------|-------------------------------------------------------|
| Weight                                                                     | 0.91 kg                                               |
| Fan size                                                                   | 143 mm                                                |
| Rotor surface                                                              | Rotor open, painted black                             |
| Blade material                                                             | Sheet steel, painted black                            |
| Fan housing material                                                       | Die-cast aluminum, painted black                      |
| Number of blades                                                           | 5                                                     |
| Airflow direction                                                          | "V"                                                   |
| Direction of rotation                                                      | Counterclockwise, viewed toward rotor                 |
| Degree of protection                                                       | IP20                                                  |
| Insulation class                                                           | "B"                                                   |
| Max. permitted ambient temp. for motor (transport/storage)                 | + 80 °C                                               |
| Min. permitted ambient temp. for motor (transport/storage)                 | - 40 °C                                               |
| Installation position                                                      | Any                                                   |
| Condensation drainage holes                                                | None, open rotor                                      |
| Mode                                                                       | S1                                                    |
| Motor bearing                                                              | Ball bearing                                          |
| Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system) | < 0.75 mA                                             |
| Electrical hookup                                                          | With plug                                             |
| Motor protection                                                           | Thermal overload protector (TOP) internally connected |
| Protection class                                                           | I (with customer connection of protective earth)      |
| Motor capacitor according to EN 60252-1 in safety protection class         | P0/S0                                                 |
| Conformity with standards                                                  | EN 60335-1; CCC;UL;EAC                                |
| Approval                                                                   | CCC; CSA C22.2 No. 113; UL 507; EAC                   |




Product drawing




All dimensions in mm.

|   |                                                     |
|---|-----------------------------------------------------|
| 1 | Direction of air flow "V"                           |
| 2 | connector: AMP 160645-2; plug housing: AMP 480053-1 |

Connection diagram



Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-58509-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.


Measured values

|   | U   | f  | n                 | P <sub>e</sub> | I    | q <sub>v</sub>    | P <sub>fs</sub> | q <sub>v</sub> | P <sub>fs</sub>    |
|---|-----|----|-------------------|----------------|------|-------------------|-----------------|----------------|--------------------|
|   | V   | Hz | min <sup>-1</sup> | W              | A    | m <sup>3</sup> /h | Pa              | cfm            | inH <sub>2</sub> O |
| 1 | 230 | 50 | 2800              | 26             | 0.13 | 420               | 0               | 245            | 0.00               |
| 2 | 230 | 50 | 2770              | 27             | 0.13 | 365               | 30              | 215            | 0.12               |
| 3 | 230 | 50 | 2755              | 27             | 0.13 | 310               | 50              | 185            | 0.20               |
| 4 | 230 | 50 | 2750              | 28             | 0.13 | 240               | 65              | 140            | 0.26               |

U = Power supply · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power consumption · I = Current draw · q<sub>v</sub> = Air flow · P<sub>fs</sub> = Pressure increase



Curves: Air performance 60 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-58510-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

|   | U   | f  | n                 | P <sub>e</sub> | I    | q <sub>v</sub>    | p <sub>fs</sub> | q <sub>v</sub> | p <sub>fs</sub>    |
|---|-----|----|-------------------|----------------|------|-------------------|-----------------|----------------|--------------------|
|   | V   | Hz | min <sup>-1</sup> | W              | A    | m <sup>3</sup> /h | Pa              | cfm            | inH <sub>2</sub> O |
| 1 | 230 | 60 | 3300              | 29             | 0.13 | 490               | 0               | 290            | 0.00               |
| 2 | 230 | 60 | 3210              | 31             | 0.14 | 440               | 30              | 260            | 0.12               |
| 3 | 230 | 60 | 3175              | 32             | 0.14 | 375               | 60              | 220            | 0.24               |
| 4 | 230 | 60 | 3140              | 33             | 0.14 | 280               | 85              | 165            | 0.34               |

U = Power supply · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power consumption · I = Current draw · q<sub>v</sub> = Air flow · p<sub>fs</sub> = Pressure increase

