

AC axial fan

straight blades (A series)

Fan housing with guard grille

W2E200-DE63-52 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Nominal data

Type	W2E200-DE63-52		
Motor	M2E068-CF		
Phase		1~	1~
Nominal voltage	VAC	115	115
Frequency	Hz	60	60
Method of obtaining data		fa	fa
Valid for approval/standard		UL 2111	CE
Speed (rpm)	min ⁻¹	3200	3200
Power consumption	W	80	78
Current draw	A	0.70	0.68
Capacitor	μF	6	6
Capacitor voltage	VDB	220	220
Capacitor standard			S2 (CE)
Max. ambient temperature	°C	-	65

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



AC axial fan

straight blades (A series)

Fan housing with guard grille


Technical description

Weight	3.01 kg
Fan size	200 mm
Rotor surface	Painted black
Blade material	Sheet steel, hot-dip galvanized
Guard grille material	Steel, phosphated and coated with black plastic
Airflow direction	"A"
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP44; installation- and position-dependent as per EN 60034-5
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H0+
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	< 0.75 mA
Motor protection	Thermal overload protector (TOP) internally connected
With cable	Lateral
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1; CE
Approval	CSA C22.2 No. 77; UL 2111




AC axial fan
straight blades (A series)
Fan housing with guard grille

Product drawing



- | | |
|---|--|
| 1 | Cable PVC AWG20 0.5 mm ² , 4x crimped splices |
| 2 | Airflow direction "A" |

Connection diagram




U1	blue	Z	brown	U2	black
PE	green/yellow				



AC axial fan
straight blades (A series)
Fan housing with guard grille

Curves: Air performance 60 Hz



Measurement: LU-10976-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _e	I	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa	cfm	inH2O
1	115	60	3200	78	0.68	970	0	570	0.00
2	115	60	3195	80	0.71	905	40	530	0.16
3	115	60	3155	84	0.74	805	80	475	0.32
4	115	60	3135	85	0.75	635	120	375	0.48

U = Power supply · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

