

W3G250-HH07-16 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Nominal data

Type	W3G250-HH07-16	
Motor	M3G055-CF	
Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 240
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	2330
Power consumption	W	83
Current draw	A	0.72
Max. back pressure	Pa	100
Max. back pressure	in. wg	0.4
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60


ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



Technical description


Weight	2.1 kg
Size	250 mm
Motor size	55
Rotor surface	Thick-film passivated
Blade material	Press-fitted sheet steel blank, sprayed with PP plastic
Fan housing material	Die-cast aluminum
Number of blades	7
Airflow direction	V
Direction of rotation	Counterclockwise, viewed toward rotor
Degree of protection	IP54
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H1
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None, open rotor
Mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 1.1 mA - Tach output - Power limiter - Motor current limitation - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Overvoltage detection - Thermal overload protection for electronics/motor - Line undervoltage detection
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Motor protection	Electronic motor protection
With cable	Variable
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1; CE
Approval	CSA C22.2 No. 77 + CAN/CSA-E60730-1; UL 1004-7 + 60730
Comment	Start-up time: 6 s

Product drawing




1	Airflow direction "V"
2	Cable PVC AWG22
	4x splice
3	Cable PVC AWG20
	3x splice
4	PE (green/yellow), ring terminal dia. 6.3
5	For self-tapping M5 screws
6	For self-tapping M6 screws

Connection diagram



No.	Conn.	Designation	Color	Function/assignment
	CON10	L	black	Power supply, phase, see nameplate for voltage range
	CON11	N	blue	Power supply, neutral conductor, see nameplate for voltage range
	CON12	PE	green/yellow	Protective earth
CON71	2	0-10 V / PWM	yellow	Control input 0-10 V or PWM, impedance 100 kΩ, SELV, adjustable curve
CON71	4	Tacho	white	Tach output: open collector, 1 pulse per revolution, SELV
CON71	3	10 V / max. 1,1 mA	red	Voltage output, power supply for external devices (e.g. potentiometers), SELV
CON71	1	GND	blue	Reference ground for control interface, SELV

Curves: Air performance 50 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-140462-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	m ³ /h	Pa	cfm	in. wg
1	230	50	2465	67	0.59	62	69	1700	0	1000	0.00
2	230	50	2410	75	0.65	61	69	1530	40	900	0.16
3	230	50	2370	81	0.68	61	68	1385	70	815	0.28
4	230	50	2330	83	0.72	62	69	1125	100	660	0.40
5	230	50	2100	42	0.36	58	65	1450	0	855	0.00
6	230	50	2100	50	0.43	58	65	1335	30	785	0.12
7	230	50	2100	56	0.47	58	65	1230	55	725	0.22
8	230	50	2100	62	0.52	59	66	1020	83	600	0.33
9	230	50	1800	26	0.23	54	61	1245	0	730	0.00
10	230	50	1800	31	0.27	54	61	1145	22	675	0.09
11	230	50	1800	35	0.30	54	61	1055	41	620	0.16
12	230	50	1800	39	0.33	55	62	875	61	515	0.24
13	230	50	1500	15	0.13	49	57	1035	0	610	0.00
14	230	50	1500	18	0.16	50	57	950	16	560	0.06
15	230	50	1500	20	0.17	49	57	880	28	515	0.11
16	230	50	1500	23	0.19	50	58	730	43	430	0.17

U = Voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
q_v = Air flow · p_{fs} = Pressure increase

