

W3G250-HL53-50 ebmpapst Datasheet  
sales@fansco.com  
www.fansco.com

Nominal data

|                          |                   |            |
|--------------------------|-------------------|------------|
| Type                     | W3G250-HL53-50    |            |
| Motor                    | M3G074-CF         |            |
| Phase                    |                   | 1~         |
| Nominal voltage          | VAC               | 230        |
| Nominal voltage range    | VAC               | 200 .. 240 |
| Frequency                | Hz                | 50/60      |
| Method of obtaining data |                   | ml         |
| Speed (rpm)              | min <sup>-1</sup> | 3000       |
| Power consumption        | W                 | 165        |
| Current draw             | A                 | 1.35       |
| Max. back pressure       | Pa                | 150        |
| Max. back pressure       | in. wg            | 0.6        |
| Min. ambient temperature | °C                | -25        |
| Max. ambient temperature | °C                | 45         |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment  
Subject to change

Data according to Commission Regulation (EU) 327/2011 (EN 17166)

|                                   |   | Actual | Req. 2015 |                               |                   |      |
|-----------------------------------|---|--------|-----------|-------------------------------|-------------------|------|
| 01 Overall efficiency $\eta_{es}$ | % | 36.6   | 28.7      | 09 Power consumption $P_{ed}$ | kW                | 0.16 |
| 02 Measurement category           |   | A      |           | 09 Air flow $q_v$             | m³/h              | 1205 |
| 03 Efficiency category            |   | Static |           | 09 Pressure increase $p_{fs}$ | Pa                | 155  |
| 04 Efficiency grade N             |   | 47.9   | 40        | 10 Speed (rpm) n              | min <sup>-1</sup> | 3015 |
| 05 Variable speed drive           |   | Yes    |           | 11 Specific ratio*            |                   | 1.00 |

Data obtained at optimum efficiency level.  
The ErP data is determined using a motor-impeller combination in a standardized measurement setup.


\* Specific ratio =  $1 + p_s / 100\,000\text{ Pa}$  LU-186141



## Technical description


|                                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|----------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Weight                                                                     | 3.5 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Size                                                                       | 250 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Motor size                                                                 | 74                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Rotor surface                                                              | Thick-film passivated                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Blade material                                                             | PP plastic                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Fan housing material                                                       | Die-cast aluminum                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Number of blades                                                           | 7                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Airflow direction                                                          | V                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Direction of rotation                                                      | Counterclockwise, viewed toward rotor                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Degree of protection                                                       | IP54; installation- and position-dependent                                                                                                                                                                                                                                                                                                                                                                                                               |
| Insulation class                                                           | "B"                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Moisture (F) / Environmental (H) protection class                          | H1                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Max. permitted ambient temp. for motor (transport/storage)                 | + 80 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Min. permitted ambient temp. for motor (transport/storage)                 | - 40 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Installation position                                                      | Any                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Condensation drainage holes                                                | None, open rotor                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Cooling hole/opening                                                       | On rotor side                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Mode                                                                       | S1                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Motor bearing                                                              | Ball bearing                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Technical features                                                         | <ul style="list-style-type: none"> <li>- Output 10 VDC, max. 10 mA</li> <li>- Tach output</li> <li>- Power limiter</li> <li>- Motor current limitation</li> <li>- Soft start</li> <li>- Control input 0-10 VDC / PWM</li> <li>- Control interface with SELV potential safely disconnected from the mains</li> <li>- Overvoltage detection</li> <li>- Thermal overload protection for electronics/motor</li> <li>- Line undervoltage detection</li> </ul> |
| EMC immunity to interference                                               | According to EN 61000-6-2 (industrial environment)                                                                                                                                                                                                                                                                                                                                                                                                       |
| EMC interference emission                                                  | According to EN 61000-6-4 (industrial environment)                                                                                                                                                                                                                                                                                                                                                                                                       |
| Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system) | ≤ 3.5 mA                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Electrical hookup                                                          | Terminal strip                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Motor protection                                                           | Electronic motor protection                                                                                                                                                                                                                                                                                                                                                                                                                              |
| With cable                                                                 | Variable                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Protection class                                                           | I (with customer connection of protective earth)                                                                                                                                                                                                                                                                                                                                                                                                         |
| Conformity with standards                                                  | EN 60335-1; CE                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Approval                                                                   | UL 1004-7 + 60730-1; CSA C22.2 No. 77 + CAN/CSA-E60730-1                                                                                                                                                                                                                                                                                                                                                                                                 |

## Product drawing




|   |                                                                  |
|---|------------------------------------------------------------------|
| 1 | Airflow direction "V"                                            |
| 2 | For self-tapping M5 screws                                       |
| 3 | Guard grill (steel, coated with white-aluminum plastic RAL 9006) |
| 4 | Guard grill (steel, coated with black plastic RAL 9005)          |

## Connection diagram



| No. | Conn. | Designation | Color        | Function/assignment                                                                                                  |
|-----|-------|-------------|--------------|----------------------------------------------------------------------------------------------------------------------|
|     | CON10 | L           | black        | Supply connection, power supply, phase, see nameplate for voltage range                                              |
|     | CON11 | N           | blue         | Supply connection, power supply, neutral conductor, see nameplate for voltage range                                  |
|     | CON12 | PE          | green/yellow | Ground connection                                                                                                    |
|     | 2     | 0- 10V PWM  | yellow       | 0-10 V / PWM control input, Ri=100 kΩ, SELV                                                                          |
|     | 4     | Tach        | white        | Tach output, open collector, 1 pulse per revolution, Isink max = 10 mA, SELV                                         |
|     | 3     | +10 V       | red          | Fixed voltage output 10 VDC +/-3 %, Imax. 10 mA, short-circuit-proof, power supply for ext. devices (e.g. pot), SELV |
|     | 1     | GND         | blue         | Reference ground for control interface, SELV                                                                         |

## Curves: Air performance 50 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-186141-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

|    | Wired | U   | f  | n                 | P <sub>ed</sub> | I    | q <sub>v</sub>    | p <sub>fs</sub> | q <sub>v</sub> | p <sub>fs</sub> |
|----|-------|-----|----|-------------------|-----------------|------|-------------------|-----------------|----------------|-----------------|
|    |       | V   | Hz | min <sup>-1</sup> | W               | A    | m <sup>3</sup> /h | Pa              | cfm            | in. wg          |
| 1  | 1~    | 230 | 50 | 3100              | 139             | 1.15 | 2015              | 0               | 1185           | 0.00            |
| 2  | 1~    | 230 | 50 | 3060              | 151             | 1.24 | 1845              | 50              | 1085           | 0.20            |
| 3  | 1~    | 230 | 50 | 3015              | 160             | 1.31 | 1625              | 100             | 955            | 0.40            |
| 4  | 1~    | 230 | 50 | 3000              | 165             | 1.35 | 1225              | 150             | 720            | 0.60            |
| 5  | 1~    | 230 | 50 | 2600              | 82              | 0.68 | 1690              | 0               | 995            | 0.00            |
| 6  | 1~    | 230 | 50 | 2600              | 93              | 0.76 | 1570              | 38              | 925            | 0.15            |
| 7  | 1~    | 230 | 50 | 2600              | 103             | 0.84 | 1400              | 75              | 825            | 0.30            |
| 8  | 1~    | 230 | 50 | 2600              | 104             | 0.85 | 1055              | 113             | 620            | 0.45            |
| 9  | 1~    | 230 | 50 | 2200              | 50              | 0.41 | 1430              | 0               | 840            | 0.00            |
| 10 | 1~    | 230 | 50 | 2200              | 56              | 0.46 | 1325              | 27              | 780            | 0.11            |
| 11 | 1~    | 230 | 50 | 2200              | 62              | 0.51 | 1185              | 53              | 695            | 0.21            |
| 12 | 1~    | 230 | 50 | 2200              | 63              | 0.51 | 895               | 81              | 525            | 0.33            |
| 13 | 1~    | 230 | 50 | 1800              | 27              | 0.22 | 1170              | 0               | 690            | 0.00            |
| 14 | 1~    | 230 | 50 | 1800              | 31              | 0.25 | 1085              | 18              | 640            | 0.07            |
| 15 | 1~    | 230 | 50 | 1800              | 34              | 0.28 | 970               | 36              | 570            | 0.14            |
| 16 | 1~    | 230 | 50 | 1800              | 35              | 0.28 | 730               | 54              | 430            | 0.22            |

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P<sub>ed</sub> = Power consumption · I = Current draw · q<sub>v</sub> = Air flow · p<sub>fs</sub> = Pressure increase

