

EC axial fan

sickled blades (S series), single inlet
with full round nozzle, for railway applications

W3G300-CT72-90 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	W3G300-CT72-90	
Motor	M3G074-CF	
Nominal voltage	VDC	80
Nominal voltage range	VDC	56 .. 100
Type of data definition		ml
Speed (rpm)	min ⁻¹	1530
Power input	W	77
Current draw	A	0.96
Max. back pressure	Pa	70
Min. ambient temperature	°C	-40
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations



EC axial fan

sickled blades (S series), single inlet
with full round nozzle, for railway applications

Technical features


Mass	4.3 kg
Size	300 mm
Motor size	74
Surface of rotor	Coated in black
Material of electronics housing	Die-cast aluminium
Material of impeller	Plastic PA, round sheet-metal plate coated in black
Material of wall ring	Sheet steel, galvanised and coated in black plastic (RAL 9005)
Material of guard grille	Steel, coated in black plastic (RAL9005)
Number of blades	5
Direction of air flow	A
Direction of rotation	Clockwise, seen on rotor
Type of protection	IP44
Insulation class	"B"
Humidity (F) / environmental protection class (H)	H3
Max. permissible ambient motor temp. (transp./ storage)	+80 °C
Min. permissible ambient motor temp. (transp./storage)	-40 °C
Mounting position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	Rotor-side
Operation mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 10 mA - Alarm relay - Run monitoring - Output limit - Motor current limit - Soft start - Control input 0-10 VDC / PWM - Over-temperature protected electronics / motor - Reverse polarity protection
Motor protection	Thermal overload protector (TOP) wired internally
Cable exit	Variable
Protection class	I (if protective earth is connected by customer)
Product conforming to standard	EN 15085-1, CPC3: 2007; EN 50155: 2008; EN 61373, Cat. 1B: 2010; CE
Approval	EAC
Remark	A prerequisite for operation is a Class 1 vehicle electrical system architecture according to EN 50533; if mains potential (e.g. 230 VAC) is passed through the alarm relay, the reinforced insulation property of the SELV signal wires will be lost and they will then only have basic insulation The SELV property (reinforced insulation) is not lost when voltages of up to 110 VDC are passed through the alarm relay.



EC axial fan

sickled blades (S series), single inlet
with full round nozzle, for railway applications

Product drawing




1	Direction of air flow "A"
2	Connection line, halogen-free, railway application EN 45545, 3x 0.33 mm ²
	3x core-end sleeve
3	Connection line, halogen-free, railway application EN 45545, 5G 1.0 mm ²
	5x core-end sleeve

EC axial fan

sickled blades (S series), single inlet
with full round nozzle, for railway applications

Connection screen




No.	Conn.	Designation	Colour	Function / assignment
1	1, 2	PE	green/yellow	Protective earth
1	3	-	blue	Power supply, GND
1	4	+	red	Power supply
1	5	NC	white 2	Floating status contact (0.3 A - 110 VDC, 1A - 60 VDC, 3A - 30 VDC), closed at n>= 100 rpm, break for failure
1	6	COM	white 1	Floating status contact, closed at n>= 100 rpm, break for failure
2	8	0-10 V	yellow	Control input, set value 0-10 VDC, impedance 100 kΩ; SELV
2	11	10 VDC	red	Voltage output 10 VDC (±3%), max. 10 mA, power supply for external devices (e.g. potentiometer); SELV
2	12	GND	blue	Reference earth for control interface; SELV



EC axial fan

sickled blades (S series), single inlet
with full round nozzle, for railway applications

Charts: Air flow



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-166499-1
Measurement: LU-166345-1
Measurement: LU-166498-1

Air performance measured as per ISO 5801
Installation category A. For detailed
information on the measuring set-up, please
contact ebm-papst. Suction-side noise
levels: LwA measured as per ISO 13347 /
LpA measured with 1m distance to fan axis.
The values given are valid under the
measuring conditions mentioned above and
may vary according to the actual installation
situation. With any deviation from the
standard set-up, the specific values have to
be checked and reviewed with the unit
installed.

Measured values

	U	n	P _{ed}	I	q _v	p _{fs}	q _v	p _{fs}
	V	min ⁻¹	W	A	m ³ /h	Pa	cfm	in. wg
1	100	1720	73	0.73	2090	0	1230	0.00
2	100	1695	80	0.80	1755	34	1030	0.14
3	100	1675	85	0.85	1495	58	880	0.23
4	100	1645	90	0.90	1175	80	690	0.32
5	80	1605	60	0.75	1950	0	1145	0.00
6	80	1580	66	0.82	1640	30	965	0.12
7	80	1565	69	0.86	1390	50	820	0.20
8	80	1530	77	0.96	1100	70	645	0.28
9	56	1155	24	0.43	1380	0	815	0.00
10	56	1145	26	0.46	1175	15	690	0.06
11	56	1135	27	0.49	1015	27	600	0.11
12	56	1120	29	0.53	805	38	475	0.15

U = Supply voltage · n = Speed (rpm) · P_{ed} = Power input · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

