

EC axial fan - AxiCool

sickle-shaped blades (S series)
Fan housing with guard grille



W3G300-JK13-34 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	W3G300-JK13-34	
Motor	M3G055-CF	
Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 240
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	1500
Power consumption	W	85
Current draw	A	0.8
Max. back pressure	Pa	80
Max. back pressure	inH2O	0.32
Min. ambient temperature	°C	-40
Max. ambient temperature	°C	40

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



Technical description


Weight	2.6 kg
Fan size	300 mm
Rotor surface	Thick-film passivated
Blade material	PP plastic
Fan housing material	PP plastic
Guard grille material	Steel, coated with black plastic (RAL 9005)
Number of blades	5
Airflow direction	"A"
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP54
Insulation class	"B"
Max. permitted ambient temp. for motor (transport/storage)	+ 70 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None, open rotor
Mode	S1
Motor bearing	Ball bearing with low-temperature lubricant
Technical features	- Speed setting input (230 V) - Power limiter - Motor current limitation - Soft start - Thermal overload protection for electronics/motor - Line undervoltage detection
Speed levels	2
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC circuit feedback	According to EN 61000-3-2/3
EMC interference emission	According to EN 61000-6-3 (household environment)
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Motor protection	Locked-rotor protection
With cable	Variable
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1; CE
Approval	UL 1004-7 + 60730; C22.2 No.77 + CAN/CSA-E60730-1

EC axial fan - AxiCool

sickle-shaped blades (S series)

Fan housing with guard grille

Product drawing




1	Direction of air flow "A"
2	Cable PVC 4G AWG20, 4x crimped splices
3	Mounting dimensions



EC axial fan - AxiCool

sickle-shaped blades (S series)
Fan housing with guard grille


Connection diagram



No.	Conn.	Designation	Color	Function/assignment
	CON 10	L	black	Power supply 230 VAC, 50-60 Hz, see nameplate for voltage range
	CON 11	N	blue	Neutral conductor
	CON 12	PE	green/yellow	Protective earth
	CON 70	SL	brown	Speed selection: switch open speed 1 (fast), switch closed speed 2 (slow)



Curves: Air performance 50 Hz



$$\rho = 1.181 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-152176-1
Measurement: LU-152177-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	m³/h	Pa	cfm	inH ₂ O
1	230	50	1685	74	0.70	60	68	2310	0	1360	0.00
2	230	50	1630	80	0.76	58	66	2015	30	1185	0.12
3	230	50	1560	84	0.79	56	64	1655	60	975	0.24
4	230	50	1500	85	0.80	55	62	1145	80	675	0.32
5	230	50	1515	54	0.53	58	65	2075	0	1220	0.00
6	230	50	1470	59	0.57	57	64	1820	25	1070	0.10
7	230	50	1435	63	0.61	55	62	1505	50	885	0.20
8	230	50	1385	69	0.66	53	60	1075	71	635	0.29

U = Power supply · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
q_v = Air flow · p_{fs} = Pressure increase

