

EC axial fan - HyBlade

sickle-shaped blades (S series)

Fan housing with guard grille

W3G450-CC38-41 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Nominal data

Type	W3G450-CC38-41	
Motor	M3G084-FA	
Phase		1~
Nominal voltage	VAC	115
Nominal voltage range	VAC	100 .. 130
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	1300
Power consumption	W	345
Current draw	A	4.0
Max. back pressure	Pa	120
Max. back pressure	in. wg	0.48
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change



EC axial fan - HyBlade

sickle-shaped blades (S series)

Fan housing with guard grille

Technical description

Size	450 mm
Motor size	84
Rotor surface	Painted black
Electronics housing material	Die-cast aluminum
Blade material	Press-fitted sheet steel blank, sprayed with PP plastic
Fan housing material	Sheet steel, galvanized and coated with black plastic (RAL 9005)
Guard grille material	Steel, coated with black plastic (RAL 9005)
Number of blades	5
Airflow direction	V
Direction of rotation	Counterclockwise, viewed toward rotor
Degree of protection	IP54
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H2
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 1.1 mA - Alarm relay - Motor current limitation - PFC, passive - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Thermal overload protection for electronics/motor - Line undervoltage detection
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Motor protection	Thermal overload protector (TOP) internally connected
With cable	Variable
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 61800-5-1
Approval	CSA C22.2 No. 77; EAC; UL 1004-3




EC axial fan - HyBlade

sickle-shaped blades (S series)

Fan housing with guard grille

Product drawing



Airflow direction "V"

Cable PVC AWG18

5x wire-end ferrule

Cable PVC AWG22

3x wire-end ferrule




EC axial fan - HyBlade


sickle-shaped blades (S series)
Fan housing with guard grille

Connection diagram

Customer circuit
Application notes for various control options



Curves: Air performance 50 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-130346-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _{ed}	I	q _v	p _{fs}	q _v	p _{fs}
		V	Hz	min ⁻¹	W	A	m ³ /h	Pa	cfm	in. wg
1	1~	115	50	1300	259	3.09	6290	0	3700	0.00
2	1~	115	50	1300	286	3.38	5680	40	3340	0.16
3	1~	115	50	1300	319	3.73	4915	80	2895	0.32
4	1~	115	50	1300	345	4.00	3825	120	2250	0.48
5	1~	115	50	1100	154	1.83	5285	0	3110	0.00
6	1~	115	50	1100	173	2.04	4790	30	2820	0.12
7	1~	115	50	1100	189	2.21	4130	57	2430	0.23
8	1~	115	50	1100	203	2.36	3220	86	1895	0.35
9	1~	115	50	900	84	1.00	4325	0	2545	0.00
10	1~	115	50	900	94	1.12	3915	20	2305	0.08
11	1~	115	50	900	103	1.21	3380	38	1990	0.15
12	1~	115	50	900	111	1.30	2635	57	1550	0.23
13	1~	115	50	700	40	0.47	3365	0	1980	0.00
14	1~	115	50	700	44	0.53	3045	12	1795	0.05
15	1~	115	50	700	49	0.57	2625	23	1545	0.09
16	1~	115	50	700	52	0.61	2050	35	1205	0.14

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · q_v = Air flow · p_{fs} = Pressure increase

