

EC axial fan - AxiCool

sickle-shaped blades (S series), single-intake
Fan housing with guard grille

W3G450-TO02-30 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	W3G450-TO02-30	
Motor	M3G074-DF	
Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 240
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	980
Power consumption	W	163
Current draw	A	1.34
Max. back pressure	Pa	74
Max. back pressure	inH2O	0.3
Min. ambient temperature	°C	-40
Max. ambient temperature	°C	40

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to ErP Directive

		Actual	Req. 2015
01 Overall efficiency η_{es}	%	39.8	28.6
02 Measurement category		A	
03 Efficiency category		Static	
04 Efficiency grade N		51.2	40
05 Variable speed drive		Yes	

Data obtained at optimum efficiency level.
The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

09 Power consumption P_{ed}	kW	0.16
09 Air flow q_v	m³/h	3505
09 Pressure increase p_{fs}	Pa	61
10 Speed (rpm) n	min ⁻¹	1000
11 Specific ratio*		1.00

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

LU-138244



EC axial fan - AxiCool

sickle-shaped blades (S series), single-intake

Fan housing with guard grille

Technical description


Weight	7.7 kg
Fan size	450 mm
Rotor surface	Galvanized
Blade material	Press-fitted sheet steel blank, sprayed with PP plastic
Fan housing material	PP plastic
Guard grille material	Steel, coated with black plastic (RAL 9005)
Number of blades	5
Airflow direction	"V"
Direction of rotation	Counterclockwise, viewed toward rotor
Degree of protection	IP54
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	F3-1
Max. permitted ambient temp. for motor (transport/storage)	+ 70 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None, open rotor
Cooling hole/opening	On rotor side
Mode	S1
Motor bearing	Ball bearing with low-temperature lubricant
Technical features	- Speed setting input (230 V) - Motor current limitation - Soft start - Thermal overload protection for electronics/motor - Line undervoltage detection
Speed levels	2
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC circuit feedback	According to EN 61000-3-2/3
EMC interference emission	According to EN 61000-6-3 (household environment)
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Motor protection	PTC thermistor
With cable	Variable
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 60335-1; CE
Approval	CCC



EC axial fan - AxiCool

sickle-shaped blades (S series), single-intake
Fan housing with guard grille

Product drawing




- | | |
|---|--|
| 1 | Direction of air flow "V" |
| 2 | Cable PVC 4G 0.5 mm², 4x crimped splices |
| 3 | Mounting dimensions |



EC axial fan - AxiCool

sickle-shaped blades (S series), single-intake
Fan housing with guard grille

Connection diagram




No.	Conn.	Designation	Color	Function/assignment
	CON 10	L	black	Power supply 230 VAC, 50-60 Hz, see nameplate for voltage range
	CON 11	N	blue	Neutral conductor
	CON 12	PE	green/yellow	Protective earth
	CON 70	SL	brown	Speed selection: switch open speed 1; switch closed speed 2



EC axial fan - AxiCool

sickle-shaped blades (S series), single-intake
Fan housing with guard grille

Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-156583-1
Measurement: LU-156686-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	qv	p _{fs}	qv	p _{fs}
	V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	m³/h	Pa	CFM	inH ₂ O
1	230	50	1105	163	1.34	63	69	5400	0	3180	0.00
2	230	50	1055	163	1.34	61	67	4715	25	2775	0.10
3	230	50	1010	163	1.34	57	63	3845	50	2260	0.20
4	230	50	980	163	1.34	62	69	2505	74	1475	0.30
5	230	50	955	104	0.89	60	65	4660	0	2740	0.00
6	230	50	935	114	0.97	57	63	4145	19	2440	0.08
7	230	50	920	122	1.03	55	61	3475	41	2045	0.16
8	230	50	895	130	1.10	60	67	2325	63	1370	0.25

U = Power supply · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
qv = Air flow · p_{fs} = Pressure increase

