

EC axial fan - HyBlade

sickled blades (S series)
with full square nozzle

W3G630-GD03-A3 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	W3G630-GD03-A3	
Motor	M3G084-GF	
Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 277
Frequency	Hz	50/60
Type of data definition		ml
Speed (rpm)	min ⁻¹	800
Power input	W	280
Current draw	A	1.2
Max. back pressure	Pa	75
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations

Data according to ErP directive

		Actual	Request 2015
01 Overall efficiency η_{es}	%	42.3	29.8
02 Measurement category		A	
03 Efficiency category		Static	
04 Efficiency grade N		52.5	40
05 Variable speed drive		Yes	

Data definition with optimum efficiency.
The ErP data is determined using a motor-impeller combination in a standardised measurement configuration.

09 Power input P_{ed}	kW	0.24
09 Air flow q_v	m³/h	6570
09 Pressure increase p_{fs}	Pa	52
10 Speed (rpm) n	min ⁻¹	805
11 Specific ratio*		1.00

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

LU-126911



Technical features


Mass	20 kg
Size	630 mm
Surface of rotor	Coated in black
Material of blades	Press-fitted sheet steel blank, sprayed with PP plastic
Material of wall ring	Sheet steel, pre-galvanised and coated in black plastic (RAL 9005)
Material of guard grille	Steel, coated in black plastic (RAL9005)
Number of blades	5
Direction of air flow	"V"
Direction of rotation	Counter-clockwise, seen on rotor
Type of protection	IP 54; Depending on installation and position
Insulation class	"B"
Humidity (F)/environmental protection class (H)	F4-1
Max. permissible ambient motor temp. (transp./ storage)	+80 °C
Min. permissible ambient motor temp. (transp./storage)	-40 °C
Mounting position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensate discharge holes	Rotor-side
Operation mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 10 mA - Alarm relay - Motor current limit - PFC, active - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Over-temperature protected electronics / motor - Line undervoltage / phase failure detection
EMC interference immunity	Acc. to EN 61000-6-2 (industrial environment)
EMC harmonics	Acc. to EN 61000-3-2/3
EMC interference emission	Acc. to EN 61000-6-3 (household environment)
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	<= 3.5 mA
Motor protection	Thermal overload protector (TOP) wired internally
Cable exit	Variable
Protection class	I (if protective earth is connected by customer)
Product conforming to standard	EN 61800-5-1

EC axial fan - HyBlade

sickled blades (S series)

with full square nozzle

Product drawing




- | | |
|---|--|
| 1 | Direction of air flow "V" |
| 2 | Connection line PVC AWG18, 5x crimped core-end sleeves |
| 3 | Connection line PVC AWG22, 3x crimped core-end sleeves |





Connection screen

Customer circuit

Full speed




Speed setting

Speed setting
via potentiometer


Connection

Fan / motor



No.	Conn.	Designation	Colour	Function / assignment
1	1, 2	PE	green/yellow	Protective earth
1	3	N	blue	Supply voltage, neutral conductor, voltage range see rating plate, 50 / 60 Hz
1	4	L	black	Supply voltage, phase, voltage range see rating plate, 50 / 60 Hz
1	5	COM	white 1	Floating status message contact, normally closed connection (2 A, max. 250 VAC, min. 10 mA)
1	6	NC	white 2	Floating status message contact, normally closed connection
2	8	0 - 10 V	yellow	Control input, set value 0 - 10 VDC, impedance 100 kOhm, SELV
2	10	P	orange	Not assigned
2	11	10 VDC	red	Voltage output 10 VDC (+/-3%), max. 10 mA, supply voltage for ext. devices (e.g. potentiometer), SELV
2	12	GND	blue	Reference mass for control interface, SELV

Charts: Air flow 50 Hz



Measurement: LU-126911-1

Air performance measured as per ISO 5801
Installation category A. For detailed
information on the measuring set-up, please
contact ebm-papst. Suction-side noise
levels: LwA measured as per ISO 13347 /
LpA measured with 1m distance to fan axis.
The values given are valid under the
measuring conditions mentioned above and
may vary according to the actual installation
situation. With any deviation from the
standard set-up, the specific values have to
be checked and reviewed with the unit
installed.

Measured values

	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	LwA _{out}	q _v	p _{fs}	q _v	p _{fs}
	V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	m³/h	Pa	cfm	inH2O
1	230	50	800	170	0.76	56	63	62	8985	0	5290	0.00
2	230	50	800	211	0.93	57	63	62	8015	25	4715	0.10
3	230	50	800	245	1.08	57	63	62	6745	50	3970	0.20
4	230	50	800	280	1.20	60	67	67	5010	75	2950	0.30
5	230	50	665	96	0.43	52	59	58	7420	0	4365	0.00
6	230	50	665	119	0.53	53	59	58	6620	17	3895	0.07
7	230	50	665	138	0.61	53	59	58	5565	34	3275	0.14
8	230	50	665	155	0.68	56	63	63	4135	51	2435	0.20
9	230	50	530	49	0.22	47	54	53	5915	0	3480	0.00
10	230	50	530	60	0.27	48	54	53	5275	11	3105	0.04
11	230	50	530	70	0.31	48	54	53	4435	22	2610	0.09
12	230	50	530	79	0.35	51	58	58	3295	33	1940	0.13
13	230	50	400	21	0.09	41	48	47	4465	0	2625	0.00
14	230	50	400	26	0.11	42	47	47	3980	6	2345	0.02
15	230	50	400	30	0.13	42	48	47	3350	12	1970	0.05
16	230	50	400	34	0.15	45	52	52	2485	19	1465	0.08

U = Supply voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power input · I = Current draw · LpA_{in} = Sound pressure level inlet side · LwA_{in} = Sound power level inlet side · LwA_{out} = Sound power level outlet side
q_v = Air flow · p_{fs} = Pressure increase