

W3G630-KL06-G1 ebmpapst Datasheet
sales@fansco.com
www.fansco.com

Nominal data

Type	W3G630-KL06-G1	
Motor	M3G084-FA	
Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 277
Frequency	Hz	50/60
Type of data definition		ml
Speed (rpm)	min ⁻¹	770
Power input	W	220
Current draw	A	0.95
Max. back pressure	Pa	70
Min. ambient temperature	°C	-40
Max. ambient temperature	°C	40

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations

Data in accordance with ecodesign regulation EU 327/2011

		Actual	Request 2015
01 Overall efficiency η_{es}	%	48.9	29.4
02 Measurement category		A	
03 Efficiency category		Static	
04 Efficiency grade N		59.5	40
05 Variable speed drive		Yes	

Data definition with optimum efficiency.
The ErP data is determined using a motor-impeller combination in a standardised measurement configuration.

09 Power input P_{ed}	kW	0.21
09 Air flow q_v	m³/h	5045
09 Pressure increase p_{fs}	Pa	67
10 Speed (rpm) n	min ⁻¹	775
11 Specific ratio*		1.00

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

LU-181832




Technical features

Mass	12.5 kg
Size	630 mm
Motor size	84
Surface of rotor	Coated in black
Material of electronics housing	Die-cast aluminium, coated in black
Material of blades	Press-fitted sheet steel blank, sprayed with PP plastic
Material of wall ring	PP plastic
Streamer material	PP plastic
Material of guard grille	Steel, coated in black plastic (RAL9005)
Number of blades	5
Direction of air flow	V
Direction of rotation	Counter-clockwise, seen on rotor
Type of protection	IP55
Insulation class	"F"
Humidity (F) / environmental protection class (H)	H2
Note ambient temperature	If there is a risk of ice formation, the fan is only to be operated with a heating tape in the wall ring. Contact ebm-papst for more details. As a fan only suitable for use with industrial evaporators
Max. permissible ambient motor temp. (transp./ storage)	+70 °C
Min. permissible ambient motor temp. (transp./storage)	-40 °C
Mounting position	See fitting instructions
Condensation drainage holes	Rotor-side
Operation mode	S1
Motor bearing	Ball bearing with anti-freezing grease
Technical features	- Output 10 VDC, max. 10 mA - Operation and alarm display - Tach output - Alarm relay - Integrated PID controller - Output limit - Motor current limit - PFC, active - RS485 MODBUS RTU - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Over-temperature protected electronics / motor - Line undervoltage / phase failure detection
EMC interference immunity	Acc. to EN 61000-6-2 (industrial environment)
EMC harmonics	Acc. to EN 61000-3-2/3
EMC interference emission	Acc. to EN 61000-6-3 (household environment)
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	<= 3.5 mA
Motor protection	Thermal overload protector (TOP) wired internally
Protection class	I (if protective earth is connected by customer)


Product conforming to standard	EN 60335-1; EN 61800-5-1; CE
Approval	UL 1004-7 + 60730; EAC; CSA C22.2 no. 77 + CAN/CSA-E60730-1



Product drawing




1	Direction of air flow "V"
2	Connection line PVC AWG22, 5x crimped core-end sleeves
3	Connection line PVC AWG18, 5x crimped core-end sleeves
4	Mounting holes for FlowGrid




- | | |
|---|---|
| 1 | Installation position: shaft horizontal (install the support struts in X-position only as shown in illustration) or rotor on bottom |
| 2 | Cable exit must be at bottom right when shaft is installed in horizontal position. |

Connection screen



No.	Conn.	Designation	Colour	Function / assignment
1	1, 2	PE	green/yellow	Protective earth
1	3	N	blue	Power supply, neutral conductor, 50/60 Hz
1	5	L	black	Power supply, phase, 50/60 Hz
1	6	NC	white 1	Status relay, floating status contact, break for failure, contact rating 250 VAC / 2 A (AC1) min. 10 mA, basic insulation on mains side and reinforced insulation on control interface side
1	7	COM	white 2	Status relay, floating status contact, break for failure, contact rating 250 VAC / 2 A (AC1) min. 10 mA, basic insulation on mains side and reinforced insulation on control interface side
2	8	0-10 V	yellow	Analogue input (set value) SELV, 0-10 V, Ri=100kΩ, parametrisable curve
2	9	Tacho	grey	Tach output: Open collector, 1 pulse per revolution, Isink max = 10 mA; SELV
2	10	RSB	brown	RS-485 interface for MODBUS, RSB; SELV
2	11	RSA	white	RS-485 interface for MODBUS, RSA; SELV
2	12	GND	blue	Signal ground for control interface, SELV
2	13	+10 V	red	Fixed voltage output 10 VDC, +10 V ±3%, max. 10 mA, short-circuit-proof, power supply for external devices (e.g. potentiometers); SELV

Charts: Air flow 50 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-181832-1

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

Measured values

	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	LwA _{out}	q _v	P _{fs}	q _v	P _{fs}
	V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	m ³ /h	Pa	cfm	in. wg
1	230	50	770	153	0.68	57	63	65	8150	0	4795	0.00
2	230	50	770	183	0.80	57	63	64	7305	25	4300	0.10
3	230	50	770	209	0.91	59	66	67	6210	50	3655	0.20
4	230	50	770	220	0.95	64	71	72	4645	70	2735	0.28
5	230	50	700	114	0.50	54	61	62	7380	0	4345	0.00
6	230	50	700	137	0.60	55	61	62	6630	21	3905	0.08
7	230	50	700	156	0.68	57	64	64	5625	41	3310	0.16
8	230	50	700	161	0.70	61	69	69	4210	58	2480	0.23
9	230	50	600	72	0.32	50	57	58	6325	0	3720	0.00
10	230	50	600	86	0.38	51	57	58	5685	15	3345	0.06
11	230	50	600	98	0.43	53	60	60	4825	30	2840	0.12
12	230	50	600	102	0.44	58	65	65	3610	42	2125	0.17
13	230	50	500	41	0.18	46	52	54	5270	0	3100	0.00
14	230	50	500	50	0.22	46	53	53	4735	11	2790	0.04
15	230	50	500	57	0.25	48	55	56	4020	21	2365	0.08
16	230	50	500	59	0.26	53	60	61	3005	29	1770	0.12

U = Supply voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power input · I = Current draw · LpA_{in} = Sound pressure level inlet side · LwA_{in} = Sound power level inlet side · LwA_{out} = Sound power level outlet side
q_v = Air flow · P_{fs} = Pressure increase

