

AC axial fan

sickled blades (S series)

with full square nozzle

W4D630-DJ01-07 ebmpapst Datasheet

sales@fansco.com

www.fansco.com



Nominal data

Type	W4D630-DJ01-07		
Motor	M4D138-LA		
Phase		3~	3~
Nominal voltage	VAC	400	400
Connection		Δ	Y
Frequency	Hz	50	50
Type of data definition		ml	ml
Valid for approval / standard		CE	CE
Speed	min ⁻¹	1340	1045
Power input	W	2530	1640
Current draw	A	4.95	2.88
Max. back pressure	Pa	240	145
Max. ambient temperature	°C	60	60
Starting current	A	19	11.5

ml = max. load · me = max. efficiency · fa = running at free air · cs = customer specs · cu = customer unit
Subject to alterations

Data according to ErP directive

Installation category	A	Overall efficiency η_{es}	32.8	32.1	36.1
Efficiency category	Static	Efficiency grade N	36.7	36	40
Variable speed drive	No	Power input P_e	kW	2.47	
Specific ratio*	1.00	Air flow q_v	m³/h	12550	
		Pressure increase p_{fs}	Pa	234	
		Speed n	min ⁻¹	1340	

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

* Specific ratio = $1 + p_b / 100\,000\text{ Pa}$

Data established at point of optimum efficiency



AC axial fan

sickled blades (S series)

with full square nozzle

Technical features

Mass	41.6 kg
Size	630 mm
Surface of rotor	Cast in aluminium
Material of terminal box	ABS plastic, black
Material of blades	Die-cast aluminium
Material of wall ring	Sheet steel, pre-galvanised and coated in black plastic (RAL 9005)
Material of guard grille	Steel, coated in black plastic (RAL9005)
Number of blades	5
Blade angle	0°
Direction of air flow	"A"
Direction of rotation	Counter-clockwise, seen on rotor
Type of protection	IP 54
Insulation class	"F"
Humidity class	F3-1
Max. permissible ambient motor temp. (transp./ storage)	+ 80 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Mounting position	Any
Condensate discharge holes	On rotor and stator sides
Operation mode	S1
Motor bearing	Ball bearing
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	<= 3.5 mA
Electrical leads	Via terminal box
Motor protection	Thermal overload protector (TOP) brought out
Cable exit	Axial
Protection class	I (if protective earth is connected by customer)
Product conforming to standard	EN 60034; EN 61800-5-1; CE
Approval	VDE




AC axial fan

sickled blades (S series)

with full square nozzle

Product drawing




1	Direction of air flow "A"
2	Tightening torque 1.5 ± 0.2 Nm
3	Cable diameter: min. 7 mm, max. 14 mm; tightening torque: 2 ± 0.3 Nm

AC axial fan

sickled blades (S series)
with full square nozzle

Connection screen




Δ	Delta connection	Y	Star connection	L1	= V1 = blue
L2	= U1 = black	L3	= W1 = brown	W2	yellow
U2	green	V2	white	TOP	2 x grey
PE	green/yellow				



AC axial fan
sickled blades (S series)
with full square nozzle

Charts: Air flow 50 Hz



Measurement: LU-101073
Measurement: LU-101075

Air performance measured as per ISO 5801
Installation category A. For detailed
information on the measuring set-up, please
contact ebm-papst. Suction-side noise
levels: LwA measured as per ISO 13347 /
LpA measured with 1m distance to fan axis.
The values given are valid under the
measuring conditions mentioned above and
may vary according to the actual installation
situation. With any deviation from the
standard set-up, the specific values have to
be checked and reviewed with the unit
installed.

Measured values

	Conn.	U	f	n	P _e	I	LpA _{in}	LwA _{in}	qv	p _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	m ³ /h	Pa
1	Δ	400	50	1380	1994	4.12	74	81	20040	0
2	Δ	400	50	1365	2178	4.36	72	79	18110	81
3	Δ	400	50	1350	2343	4.55	72	78	15680	160
4	Δ	400	50	1340	2530	4.95	74	81	12620	240
5	Y	400	50	1145	1429	2.51	70	76	16600	0
6	Y	400	50	1110	1517	2.66	68	74	14710	53
7	Y	400	50	1075	1583	2.79	67	73	12490	102
8	Y	400	50	1045	1640	2.88	68	74	9905	145

Conn. = Connection · U = Supply voltage · f = Frequency · n = Speed · P_e = Power input · I = Current draw · LpA_{in} = Sound pressure level inlet side · LwA_{in} = Sound power level inlet side
qv = Air flow · p_{fs} = Pressure increase

