

AC axial fan

sickled blades (S series)

with full square nozzle

W6D800-GP01-01 ebmpapst Datasheet

sales@fansco.com

www.fansco.com

Nominal data

Type	W6D800-GP01-01		
Motor	M6D138-NA		
Phase		3~	3~
Nominal voltage	VAC	400	400
Connection		Δ	Y
Frequency	Hz	50	50
Type of data definition		ml	ml
Valid for approval / standard		CE	CE
Speed	min ⁻¹	915	740
Power input	W	2080	1430
Current draw	A	4.62	2.66
Max. back pressure	Pa	180	118
Min. ambient temperature	°C	-40	-40
Max. ambient temperature	°C	60	60
Starting current	A	18.6	6.2

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations

Data according to ErP directive

Installation category	A
Efficiency category	Static
Variable speed drive	No
Specific ratio*	1.00

* Specific ratio = $1 + p_{fs} / 100\,000\text{ Pa}$

		Actual	Request 2013	Request 2015
Overall efficiency η_{es}	%	37.1	31.4	35.4
Efficiency grade N		41.7	36	40
Power input P_e	kW	1.91		
Air flow q_v	m ³ /h	16455		
Pressure increase p_{fs}	Pa	156		
Speed n	min ⁻¹	925		

Data definition with optimum efficiency. LU-102249
The ErP data is determined using a motor-impeller combination in a standardised measurement configuration.



AC axial fan

sickled blades (S series)

with full square nozzle

Technical features


Mass	46.6 kg
Size	800 mm
Surface of rotor	Cast in aluminium
Material of terminal box	PP plastic
Material of blades	Die-cast aluminium
Material of wall ring	Sheet steel, galvanised and coated in black plastic (RAL 9005)
Material of guard grille	Steel, coated in black plastic (RAL9005)
Number of blades	5
Blade angle	0°
Direction of air flow	"V"
Direction of rotation	Clockwise, seen on rotor
Type of protection	IP 54
Insulation class	"F"
Humidity class	F3-1
Max. permissible ambient motor temp. (transp./ storage)	+ 80 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Mounting position	Any
Condensate discharge holes	On rotor and stator sides
Operation mode	S1
Motor bearing	Ball bearing
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	<= 3.5 mA
Electrical leads	Via terminal box
Motor protection	Thermal overload protector (TOP) brought out
Cable exit	Axial
Protection class	I (if protective earth is connected by customer)
Product conforming to standard	EN 60034-1 (2010); EN 61800-5-1; CE
Approval	EAC; VDE



AC axial fan

sickled blades (S series)
with full square nozzle

Product drawing




1	Direction of air flow "V"
2	Tightening torque 1.5±0.2 Nm
3	Cable diameter min. 7 mm, max. 14 mm, tightening torque 2±0.3 Nm



AC axial fan

sickled blades (S series)
with full square nozzle

Connection screen




Δ	Delta connection	Y	Star connection	L1	= U1 = black
L2	= V1 = blue	L3	= W1 = brown	W2	yellow
U2	green	V2	white	TOP	2 x grey
PE	green/yellow				



AC axial fan

sickled blades (S series)
with full square nozzle

Charts: Air flow 50 Hz



Air performance measured as per ISO 5801
Installation category A. For detailed
information on the measuring set-up, please
contact ebm-papst. Suction-side noise
levels: L_{wA} measured as per ISO 13347 /
L_{pA} measured with 1m distance to fan axis.
The values given are valid under the
measuring conditions mentioned above and
may vary according to the actual installation
situation. With any deviation from the
standard set-up, the specific values have to
be checked and reviewed with the unit
installed.

Measured values

	Conn.	U	f	n	P _e	I	L _{pA_{in}}	L _{wA_{in}}	L _{wA_{out}}	qv	p _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	m³/h	Pa
1	Δ	400	50	945	1445	3.99	67	73	73	25030	0
2	Δ	400	50	935	1645	4.18	65	72	71	22100	60
3	Δ	400	50	930	1810	4.33	66	72	71	18800	120
4	Δ	400	50	915	2080	4.62	71	77	77	14300	180
5	Y	400	50	840	1101	2.08	64	71	70	22110	0
6	Y	400	50	810	1228	2.30	62	69	68	18980	44
7	Y	400	50	780	1306	2.44	63	69	68	15780	84
8	Y	400	50	740	1430	2.66	66	73	72	11610	118

Conn. = Connection · U = Supply voltage · f = Frequency · n = Speed · P_e = Power input · I = Current draw · L_{pA_{in}} = Sound pressure level inlet side · L_{wA_{in}} = Sound power level inlet side
L_{wA_{out}} = Sound power level outlet side · qv = Air flow · p_{fs} = Pressure increase

