


COMMONWEALTH AC AXIAL FAN

FP-108X


119x119x25.4mm MERCURY

DESIGN FEATURES


- ***BEARING SYSTEM:** SLEEVE BEARING & BALL BEARING
- ***IMPELLER:** PLASTIC WITH FIBER GLASS FILLED UL 94V-0
- ***HOUSING:** DIE CAST ALUMINUM PAINTED BLACK OR NATURAL COLOR
- ***MOTOR:** SHADED POLE, IMPEDANCE PROTECTED
- ***CONNECTING:** TERMINAL & WIRE LEADS
- ***SPEED:** S-1 HIGH SPEED TYPE
S-2 MEDIUM SPEED TYPE
- ***OTHER VOLTAGE:** 24, 48, 100, 380AC (50/60Hz) ARE AVAILABLE



DIMENSIONS:MM



PERFORMANCE



SPECIFICATIONS

Specifications are subject to change without notice

MODEL NO.	VOLT (VAC)	FREQUENCY (HZ)	AIR (CFM)	VOLUME (M ³ /MIN)	CURRENT (A)	POWER (W)	SPEED (RPM)	STATIC PRESSURE (INCH-H ₂ O)	NOISE (dBA)
FP-108X (S-1)	110/120	50/60	64/80	1.8/2.3	0.19/0.18	18/16	2000/2350	0.20/0.23	42/44
FP-108X (S-1)	220/240	50/60	64/80	1.8/2.3	0.12/0.11	18/16	2000/2350	0.20/0.23	42/44
FP-108X (S-2)	110/120	50/60	57/60	1.6/1.7	0.13/0.11	13/12	1700/1900	0.16/0.18	34/37
FP-108X (S-2)	220/240	50/60	57/60	1.6/1.7	0.09/0.08	13/12	1700/1900	0.16/0.18	34/37