



SPECIFICATION FOR APPROVAL

Customer :

Description : DC FAN

Customer Part No.

REV. :

Delta Model No. : BUB0812HN-00

REV. : 01

Sample Issue No. :

Sample Issue Date : JUN.14 2021

PLEASE SEND ONE COPY OF THIS SPECIFICAITON BACK AFTER
YOU SIGNED APPROVAL FOR PRODUCTION PRE-ARRANGMENT.

APPROVED BY:

DATE :

DELTA ELECTRONICS, INC.

TAOYUAN PLANT

252, SHANGYING ROAD, GUISHAN INDUSTRIAL ZONE,
TAOYUAN CITY 33341, TAIWAN

TEL:886-(0)3-3591968

FAX:886-(0)3-3591991

DELTA ELECTRONICS, INC.
252, SHANGYING ROAD, GUISHAN INDUSTRIAL ZONE,
TAOYUAN CITY 33341, TAIWAN

TEL : 886-(0)3-3591968
FAX : 886-(0)3-3591991

STATEMENT OF DEVIATION

NONE

DESCRIPTION:

DELTA ELECTRONICS, INC.

252, SHANGYING ROAD, GUISHAN INDUSTRIAL ZONE,
TAOYUAN CITY 33341, TAIWAN

TEL : 886-(0)3-3591968
FAX : 886-(0)3-3591991

Specification For Approval

Customer :

Description : DC FAN

Customer P/N :

rev. :

Delta model no. : BUB0812HN-00

Delta Safety Model No.: BUB0812HN-00

Sample revision. : 01

Issue no.:

Sample issue date : JUN.14 2021

Quantity :

1. SCOPE:

THIS SPECIFICATION DEFINES THE ELECTRICAL AND MECHANICAL CHARACTERISTICS OF THE DC BRUSHLESS BLOWER FAN.

2. CHARACTERS:

ITEM	DESCRIPTION
RATED VOLTAGE	12 VDC
OPERATION VOLTAGE	 10.8 - 13.2 VDC
PWM MINIMUM START DUTY	30% (MAX.) @ 25KHz
OPERATION DUTY RANGE	 20% - 100% @ 25KHz
RATED CURRENT (AVG.)	 0.50 (MAX. 0.80) A SAFETY CURRENT ON LABEL: 0.80A
RATED POWER (AVG.)	 6.00 (MAX. 9.60) W
RATED SPEED	4300 ± 10% R.P.M.
MAX. AIR FLOW (AT ZERO STATIC PRESSURE)	 0.534 (MIN. 0.465) M ³ /MIN. 18.84 (MIN. 16.39) CFM
MAX. AIR PRESSURE (AT ZERO AIR FLOW)	 34.30 (MIN. 24.94) mmH ₂ O 1.350 (MIN. 0.981) inchH ₂ O
ACOUSTICAL NOISE (AVG.)	44.5 (MAX. 48.5) dB-A
INSULATION TYPE	UL: CLASS A

(continued)


PART NO:

DELTA MODEL: BUB0812HN-00

INSULATION STRENGTH	10 MEG OHM MIN. AT 500 VDC (BETWEEN FRAME AND (+) TERMINAL)
DIELECTRIC STRENGTH	5 mA MAX. AT 500 VAC 50/60 Hz ONE MINUTE, (BETWEEN FRAME AND (+) TERMINAL)
LIFE EXPECTANCE (L10) (AT RATED VOLTAGE)	50,000 HOURS CONTINUOUS OPERATION AT 40°C WITH 15 ~ 65 %RH. Δ_1
ROTATION	CLOCKWISE VIEW FROM NAME PLATE SIDE

NOTES:

1. ALL READINGS ARE MEASURED AFTER STABLY WARMING UP
THROUGH 10 MINUTES.
2. STANDARD AIR PROPERTY IS AIR AT (Td) 25°C TEMPERATURE, (RH) 65%
RELATIVE HUMIDITY , AND (Pb) 760 mmHg BAROMETRIC PRESSURE.
3. THE VALUES WRITTEN IN PARENS , (), ARE LIMITED SPEC.
4. ACOUSTICAL NOISE MEASURING CONDITION:



NOISE IS MEASURED AT RATED VOLTAGE IN FREE AIR IN SEMI-ANECHOIC
CHAMBER WITH MICROPHONE AT A DISTANCE OF ONE METER FROM THE
FAN INTAKE.

PART NO:

DELTA MODEL: BUB0812HN-00

3. MECHANICAL:

3-1. DIMENSIONS-----	SEE DIMENSIONS DRAWING
3-2. PILLOW-----	PLASTIC UL: 94V-0
3-3. IMPELLER-----	PLASTIC UL: 94V-0
3-4. COVER-----	SECC
3-5. BEARING SYSTEM-----	SLEEVE BEARING
3-6. WEIGHT-----	76.0 (REF.) GRAMS

1

4. ENVIRONMENTAL:

4-1. OPERATING TEMPERATURE-----	-10 TO +70 DEGREE C
4-2. STORAGE TEMPERATURE-----	-40 TO +75 DEGREE C
4-3. OPERATING HUMIDITY-----	5 TO 90 % RH
4-4. STORAGE HUMIDITY-----	5 TO 95 % RH

5. PROTECTION:

5-1. LOCKED ROTOR PROTECTION

IMPEDANCE OF MOTOR WINDING PROTECTS MOTOR FROM FIRE IN
96 HOURS OF LOCKED ROTOR CONDITION AT THE RATED VOLTAGE.

5-2. POLARITY PROTECTION

BE CAPABLE OF WITHSTANDING IF REVERSE CONNECTION FOR
POSITIVE AND NEGATIVE LEADS.

6. RE OZONE DEPLETING SUBSTANCES:

6-1. NO CONTAINING PBBs, PBBOs, CFCs, PBBEs, PBDPEs AND HCFCs.

7. PRODUCTION LOCATION


7-1. PRODUCTS WILL BE PRODUCED IN CHINA

1

PART NO:

DELTA MODEL: BUB0812HN-00

8. P & Q CURVE:




*TEST CONDITION: INPUT VOLTAGE----OPERATION VOLTAGE
TEMPERATURE----ROOM TEMPERATURE
HUMIDITY----65%RH

PART NO:

DELTA MODEL: BUB0812HN-00

9. DIMENSION DRAWING:



NOTES:

1. LEAD WIRE: UL1061 AWG #28
RED WIRE-----(+)
BLACK WIRE-----(-)
BLUE WIRE-----(F00)
YELLOW WIRE----(PWM)
2. THIS PRODUCT IS ROHS COMPLIANT.

PART NO:

DELTA MODEL: BUB0812HN-00


10. LABEL: 



OR



OR



THE CONTENT OF 2D BARCODE IS SHOWN AS BELOW:

2D BARCODE



SCAN →

BARCODE

BUB0812HN-00A0YYMDSSSS

① ② ③ ④

(DATA MATRIX)


①	BUB0812HN-00	P/N	DELTA MODEL NAME.
②	A0	VENDOR	"A0" MEANS DELTA.
③	YY	YEAR	"10" FOR 2010, "11" FOR 2011, ET AL.
③	M	MONTH	1-9 IS JAN-SEP, A IS OCT, B IS NOV, C IS DEC.
③	D	DATE	1-9 IS 1st-9th, A IS 10th, B IS 11th, ET AL. (NOT INCLUDED I, J, O and Q.)
④	SSSSS	SERIAL NUMBER	FROM 00001 TO 99999.

PART NO:

DELTA MODEL: BUB0812HN-00

11. FREQUENCY GENERATOR (FG) SIGNAL:

11-1. OUTPUT CIRCUIT - OPEN COLLECTOR MODE:




CAUTION:

THE LEAD WIRE OF FG SIGNAL CAN NOT TOUCH
THE LEAD WIRE OF POSITIVE OR NEGATIVE.

11-2. SPECIFICATION:


$V_{CE} \text{ (sat)} = 0.5V \text{ MAX.}$ $V_{FG} = 5.0 \text{ TYP.} (V_{CC} \text{ MAX.})$
 $I_C = 5\text{mA MAX.}$ $R \geq V_{FG} / I_C$

11-3. FREQUENCY GENERATOR WAVEFORM:



FAN RUNNING FOR 4 POLES

BLADE LOCKED



$N = \text{R.P.M.}$

$TS = 60/N(\text{SEC})$

*VOLTAGE LEVEL AFTER BLADE LOCKED


*4 POLES

PART NO:

DELTA MODEL: BUB0812HN-00

12. PWM CONTROL SIGNAL:

SIGNAL VOLTAGE RANGE: 0~5.5 VDC



*THE PREFERRED OPERATING POINT FOR THE FAN IS 25KHz.

*AT 100% DUTY CYCLE, THE ROTOR WILL SPIN AT MAXIMUM SPEED.

*AT 0% DUTY CYCLE, THE ROTOR WILL STOP.

*WITH CONTROL SIGNAL LEAD WIRE DISCONNECTED, THE FAN WILL SPIN AT MAXIMUM SPEED.

*AT RATED VOLTAGE, 25Khz, 30% DUTY CYCLE, THE FAN WILL BE ABLE TO START FROM A DEAD STOP.

12-1. SPEED VS PWM CONTROL SIGNAL:

(AT 25°C, RATED VOLTAGE & PWM FREQUENCY=25Khz)

DUTY CYCLE (%)	SPEED (R.P.M.)	CURRENT (A)
100	4300±10%	0.50 (Max. 0.80)
0	0	0.01 (Max. 0.03)

1



Application Notice

1. Delta will not guarantee the performance of the products if the application condition falls outside the parameters set forth in the specification.
2. A written request should be submitted to Delta prior to approval if deviation from this specification is required.
3. Please exercise caution when handling fans. Damage may be caused when pressure is applied to the impeller, if the fans are handled by the lead wires, or if the fan was hard-dropped to the production floor.
4. Except as pertains to some special designs, there is no guarantee that the products will be free from any such safety problems or failures as caused by the introduction of powder, droplets of water or encroachment of insect into the hub.
5. The above-mentioned conditions are representative of some unique examples and viewed as the first point of reference prior to all other information.
6. It is very important to establish the correct polarity before connecting the fan to the power source. Positive (+) and Negative (-). Damage may be caused to the fans if connection is with reverse polarity, if there is no foolproof method to protect against such error specifically mentioned in this spec.
7. Delta fans without special protection are not suitable where any corrosive fluids are introduced to their environment.
8. Please ensure all fans are stored according to the storage temperature limits specified. Do not store fans in a high humidity environment. We highly recommend performance testing is conducted before shipping, if the fans have been stored over 6 months.
9. Not all fans are provided with the Lock Rotor Protection feature. If you impair the rotation of the impeller for the fans that do not have this function, the performance of those fans will lead to failure.
10. Please be cautious when mounting the fan. Incorrect mounting of fans may cause excess resonance, vibration and subsequent noise.
11. It is important to consider safety when testing the fans. A suitable fan guard should be fitted to the fan to guard against any potential for personal injury.
12. Except where specifically stated, all tests are carried out at room (ambient) temperature and relative humidity conditions of 25°C, 65% RH. The test value is only for fan performance itself.
13. Be certain to connect an “ 4.7µF or greater” capacitor to the fan externally when the application calls for using multiple fans in parallel, to avoid any unstable power.