

8300100101
VBH0560CTTRS

EC centrifugal module - RadiPac

backward-curved, single-intake
with support bracket

ebm-papst Mulfingen GmbH & Co. KGaA & Co. KG

Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
info1@de.fansco.com
www.fansco.com

Limited partnership · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Item	8300100101	
Motor	E15034-120	
Phase		3~
Nominal voltage	VAC	400
Nominal voltage range	VAC	380 .. 480
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	2370
Power consumption	W	6500
Current draw	A	10
Min. ambient temperature	°C	-40
Max. ambient temperature	°C	40

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to Commission Regulation (EU) 327/2011 (prEN 17166)

		Actual	Req. 2015			
01 Overall efficiency η_{es}	%	75.5	59.9	09 Power consumption P_{ed}	kW	6.32
02 Measurement category		A		09 Air flow q_v	m³/h	14165
03 Efficiency category		Static		09 Pressure increase p_{fs}	Pa	1172
04 Efficiency grade N		77.6	62	10 Speed (rpm) n	min ⁻¹	2370
05 Variable speed drive		Yes		11 Specific ratio*		1.01

Data obtained at optimum efficiency level.

* Specific ratio = $1 + p_b / 100\,000\text{ Pa}$

LU-215301

The efficiency values displayed for achieving conformity with the Ecodesign Regulation EU 327/2011 has been reached with defined air duct components (e.g. inlet rings).
The dimensions must be requested from ebm-papst. If other air conduction geometries are used on the installation side, the ebm-papst evaluation loses its validity/the conformity must be confirmed again.
The product does not fall within the scope of Regulation (EU) 2019/1781 due to the exception specified in Article 2 (2a) (motors completely integrated into a product).

8300100101

VBH0560CTTRS

EC centrifugal module - RadiPac

backward-curved, single-intake

with support bracket

Technical description

Weight	54.2 kg
Size	560 mm
Motor size	150
Rotor surface	Painted black
Electronics housing material	Die-cast aluminum
Impeller material	PP plastic
Support plate material	Sheet steel, galvanized
Support bracket material	Steel, painted black
Inlet nozzle material	ABS plastic
Number of blades	5
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP55
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	H1
Ambient temperature note	Occasional start-up at temperatures between -40°C and -25°C is permitted. For continuous operation at ambient temperatures below -25°C (such as refrigeration applications), use must be made of a fan design with special low-temperature bearings.
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	See legend on product drawing
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing
Technical features	- Operation and alarm display with LED - External 15-50 VDC input (parameterization) - Alarm relay - Integrated PI controller - Configurable inputs/outputs (I/O) - MODBUS V6.4 - Motor current limitation - RS-485 MODBUS-RTU - Soft start - Voltage output 3.3-24 VDC, Pmax = 800 mW - Control interface with SELV potential safely disconnected from the mains - Thermal overload protection for electronics/motor - Line undervoltage / phase failure detection - Vibration sensor
Power Factor Correction (PFC)	Passive (through low-capacitance DC link)
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC interference emission	According to EN 61000-6-3 (household environment), except EN 61000-3-2 for professionally used equipment with a total rated power greater than 1 kW
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Electrical hookup	Terminal box
Motor protection	Electronic motor protection

8300100101
VBH0560CTTRS

EC centrifugal module - RadiPac

backward-curved, single-intake
with support bracket

Protection class assignment	I; If a protective earth is connected. The built-in component has several local protection class assignments. The final protection class is determined by the intended installation.
Conformity with standards	EN 61800-5-1; UKCA; CE
Approval	UL 1004-7 + 60730-1; CSA C22.2 No. 77 + CAN/CSA-E60730-1; EAC

8300100101


VBH0560CTTRS

EC centrifugal module - RadiPac

backward-curved, single-intake

with support bracket

Product drawing




- | | |
|---|--|
| 1 | Installed position: shaft horizontal (install support struts only vertically as illustrated) or rotor on bottom; rotor on top on request |
| 2 | Cable diameter min. 4 mm, max. 10 mm, tightening torque 4 ± 0.6 Nm |
| 3 | Cable diameter min. 5 mm, max. 14 mm, tightening torque 6 ± 0.9 Nm |
| | (The tightening torque is designed for PVC cables. If the cable materials are different, the tightening torque may have to be adjusted) |
| 4 | Tightening torque 3 ± 0.3 Nm |
| 5 | Inlet ring with pressure tap (k-factor: 381) |
| 6 | Attachment holes for FlowGrid 50710-2-2957 (not included in scope of delivery) |

EC centrifugal module - RadiPac

backward-curved, single-intake
with support bracket

Connection diagram



No.	Conn.	Designation	Function/assignment
	CON1	L1, L2, L3	Power supply, phase, see nameplate for voltage range
	PE	PE	Protective earth
	CON2	RSA	RS485 interface for MODBUS, RSA; SELV
	CON2	RSB	RS485 interface for MODBUS, RSB; SELV
	CON2	GND	Reference ground for control interface, SELV
	CON2	IO1	Function parameterizable (see "Optional interface functions" table) Factory setting: Digital input - high active, function: Disable input, SELV - inactive: Pin open or applied voltage < 1.5 VDC - active: applied voltage 3.5-50 VDC Reset function: Triggering of error reset on change of state from "enabled" to "disabled"
	CON2	IO2	Function parameterizable (see "Optional interface functions" table) Factory setting: Analog input 0-10 V/PWM, Ri=100 kΩ, function: Set value Characteristic curve parameterizable (see input characteristic curve P1-IN), SELV
	CON2	IO3	Function parameterizable (see "Optional interface functions" table) Factory setting: Analog output 0-10 V, max. 5 mA, function: Actual speed Characteristic curve parametrizable (see output characteristic curve P3-OUT), SELV
	CON2	Vout	Voltage output 3.3-24 VDC ±5%, Pmax=800 mW, voltage parameterizable Factory setting: 10 VDC short-circuit-proof, supply for external devices, SELV alternatively: 15-50 VDC input for parameterization via MODBUS without line voltage
	CON2	COM	Status relay, floating status contact, common connection, contact rating 250 VAC / 2 A (AC1) / min. 10 mA, reinforced insulation on supply side and on control interface side
	CON2	NC	Status relay, floating status contact, break for failure
		LED	green: status = good, ready for operation orange: status = warning red: status = failure
		P1-IN	Input characteristic curve
		P3-OUT	Output characteristic curve

Terminal/plug assignment

configurable option			configurable IO functions: normal / inverse	MODBUS Register for IO mode configuration	electrical specification		OUTPUT																	
CON2	configurable IO mode	◦ Din1 (active high): digital input			active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D158 [0]	◦	switch: fan enable / disable	(selected directly via IO mode)	D130 [0]	signal: fan modulation level %	D130 [1]	signal: actual speed	D130 [2]	signal: system modulation level %	D130 [5]	signal: remote control output 0-10V	D130 [4]	pulse input for auto-addressing					
		◦ Ain1 0-10V/PWM: analog input			RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	D158 [2]	◦	switch: set value source	(selected directly via IO mode)	D130 [10]	signal: tach out	D16A [...]	switch: fan enable / disable	D16C [...]	switch: direction of rotation: cw / ccw	D148 [...]	switch: control function: heating (pos.) / cooling (neg.)	D12E [...]	switch: parameter set: #1 / #2	D104 [...]	source: sensor value	D147 [...]	source: set value	D101 [...]
		◦ Tach out (open collector output)			Umax = 50VDC, Imax = 20mA, SELV	D158 [5]	◦	switch: set value source	(selected directly via IO mode)	D130 [10]	signal: tach out	D16A [...]	switch: fan enable / disable	D16C [...]	switch: direction of rotation: cw / ccw	D148 [...]	switch: control function: heating (pos.) / cooling (neg.)	D12E [...]	switch: parameter set: #1 / #2	D104 [...]	source: sensor value	D147 [...]	source: set value	D101 [...]
		◦ Diagnostics out (open collector output)			Umax = 50VDC, Imax = 20mA, SELV	D158 [6]	◦	switch: set value source	(selected directly via IO mode)	D130 [10]	signal: tach out	D16A [...]	switch: fan enable / disable	D16C [...]	switch: direction of rotation: cw / ccw	D148 [...]	switch: control function: heating (pos.) / cooling (neg.)	D12E [...]	switch: parameter set: #1 / #2	D104 [...]	source: sensor value	D147 [...]	source: set value	D101 [...]
IO1	configurable IO mode	◦ Din2 (active high): digital input			active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [0]	◦	switch: fan enable / disable	(selected directly via IO mode)	D130 [10]	signal: tach out	D16A [...]	switch: fan enable / disable	D16C [...]	switch: direction of rotation: cw / ccw	D148 [...]	switch: control function: heating (pos.) / cooling (neg.)	D12E [...]	switch: parameter set: #1 / #2	D104 [...]	source: sensor value	D147 [...]	source: set value	D101 [...]
		◦ Ain2 0-10V/PWM: analog input			RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	D159 [2]	◦	switch: set value source	(selected directly via IO mode)	D130 [10]	signal: tach out	D16A [...]	switch: fan enable / disable	D16C [...]	switch: direction of rotation: cw / ccw	D148 [...]	switch: control function: heating (pos.) / cooling (neg.)	D12E [...]	switch: parameter set: #1 / #2	D104 [...]	source: sensor value	D147 [...]	source: set value	D101 [...]
		◦ Ain2 4-20mA: analog input			RI = 125R, characteristic curve parameterizable, SELV	D159 [3]	◦	switch: set value source	(selected directly via IO mode)	D130 [10]	signal: tach out	D16A [...]	switch: fan enable / disable	D16C [...]	switch: direction of rotation: cw / ccw	D148 [...]	switch: control function: heating (pos.) / cooling (neg.)	D12E [...]	switch: parameter set: #1 / #2	D104 [...]	source: sensor value	D147 [...]	source: set value	D101 [...]
		◦ Din3 (active high): digital input			active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D15A [0]	◦	switch: fan enable / disable	(selected directly via IO mode)	D130 [10]	signal: tach out	D16A [...]	switch: fan enable / disable	D16C [...]	switch: direction of rotation: cw / ccw	D148 [...]	switch: control function: heating (pos.) / cooling (neg.)	D12E [...]	switch: parameter set: #1 / #2	D104 [...]	source: sensor value	D147 [...]	source: set value	D101 [...]
IO2	configurable IO mode	◦ Din3 (active low): digital input			active: applied voltage < 1.5VDC, SELV not active: pin open or applied voltage 3.5-50VDC	D15A [1]	◦	switch: fan enable / disable	(selected directly via IO mode)	D130 [10]	signal: tach out	D16A [...]	switch: fan enable / disable	D16C [...]	switch: direction of rotation: cw / ccw	D148 [...]	switch: control function: heating (pos.) / cooling (neg.)	D12E [...]	switch: parameter set: #1 / #2	D104 [...]	source: sensor value	D147 [...]	source: set value	D101 [...]
		◦ PWMIn3: digital input idle level high	PWM = 40Hz - 10KHz, characteristics parameterizable	D15A [7]	◦	switch: fan enable / disable	(selected directly via IO mode)	D130 [10]	signal: tach out	D16A [...]	switch: fan enable / disable	D16C [...]	switch: direction of rotation: cw / ccw	D148 [...]	switch: control function: heating (pos.) / cooling (neg.)	D12E [...]	switch: parameter set: #1 / #2	D104 [...]	source: sensor value	D147 [...]	source: set value	D101 [...]		
		◦ PWMIn3: digital input idle level low	active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV	D15A [8]	◦	switch: fan enable / disable	(selected directly via IO mode)	D130 [10]	signal: tach out	D16A [...]	switch: fan enable / disable	D16C [...]	switch: direction of rotation: cw / ccw	D148 [...]	switch: control function: heating (pos.) / cooling (neg.)	D12E [...]	switch: parameter set: #1 / #2	D104 [...]	source: sensor value	D147 [...]	source: set value	D101 [...]		
		◦ Aout3 0-10V: analog output	active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV	D15A [4]	◦	switch: fan enable / disable	(selected directly via IO mode)	D130 [10]	signal: tach out	D16A [...]	switch: fan enable / disable	D16C [...]	switch: direction of rotation: cw / ccw	D148 [...]	switch: control function: heating (pos.) / cooling (neg.)	D12E [...]	switch: parameter set: #1 / #2	D104 [...]	source: sensor value	D147 [...]	source: set value	D101 [...]		
IO3	configurable IO mode	◦ Tacho out (pulses), analog output	function parameterizable, max. 5mA max output frequency 300Hz, SELV	D15A [5]	◦	switch: fan enable / disable	(selected directly via IO mode)	D130 [10]	signal: tach out	D16A [...]	switch: fan enable / disable	D16C [...]	switch: direction of rotation: cw / ccw	D148 [...]	switch: control function: heating (pos.) / cooling (neg.)	D12E [...]	switch: parameter set: #1 / #2	D104 [...]	source: sensor value	D147 [...]	source: set value	D101 [...]		
		◦ Diagnostics out (pulses)	0-10V max. 5mA max output frequency 300Hz, SELV	D15A [6]	◦	switch: fan enable / disable	(selected directly via IO mode)	D130 [10]	signal: tach out	D16A [...]	switch: fan enable / disable	D16C [...]	switch: direction of rotation: cw / ccw	D148 [...]	switch: control function: heating (pos.) / cooling (neg.)	D12E [...]	switch: parameter set: #1 / #2	D104 [...]	source: sensor value	D147 [...]	source: set value	D101 [...]		
		◦ RS485 bus connection,	MODBUS RTU, specification V6.4, SELV		◦	switch: fan enable / disable	(selected directly via IO mode)	D130 [10]	signal: tach out	D16A [...]	switch: fan enable / disable	D16C [...]	switch: direction of rotation: cw / ccw	D148 [...]	switch: control function: heating (pos.) / cooling (neg.)	D12E [...]	switch: parameter set: #1 / #2	D104 [...]	source: sensor value	D147 [...]	source: set value	D101 [...]		
		◦ voltage output	voltage parameterizable 3.3..24VDC +/- 5%, Pmax=800mW, short-circuit-proof, supply for external devices, SELV	D16E [...]	◦	switch: fan enable / disable	(selected directly via IO mode)	D130 [10]	signal: tach out	D16A [...]	switch: fan enable / disable	D16C [...]	switch: direction of rotation: cw / ccw	D148 [...]	switch: control function: heating (pos.) / cooling (neg.)	D12E [...]	switch: parameter set: #1 / #2	D104 [...]	source: sensor value	D147 [...]	source: set value	D101 [...]		
Vout	configurable IO mode	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage	15...50VDC		◦	switch: fan enable / disable	(selected directly via IO mode)	D130 [10]	signal: tach out	D16A [...]	switch: fan enable / disable	D16C [...]	switch: direction of rotation: cw / ccw	D148 [...]	switch: control function: heating (pos.) / cooling (neg.)	D12E [...]	switch: parameter set: #1 / #2	D104 [...]	source: sensor value	D147 [...]	source: set value	D101 [...]		
		◦ voltage			◦	switch: fan enable / disable	(selected directly via IO mode)	D130 [10]	signal: tach out	D16A [...]	switch: fan enable / disable	D16C [...]	switch: direction of rotation: cw / ccw	D148 [...]	switch: control function: heating (pos.) / cooling (neg.)	D12E [...]	switch: parameter set: #1 / #2	D104 [...]	source: sensor value	D147 [...]	source: set value	D101 [...]		

For further information and additional functions see EC Control Software, Fan-Set-App, or MODBUS Parameter Specification V6.4

8300100101


VBH0560CTTRS

EC centrifugal module - RadiPac

backward-curved, single-intake

with support bracket

Curves: Air performance 50 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-215301-1
Date: 2021-07-27
Nozzle: 8217101924

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _e	I	LpA _{in}	LwA _{in}	LwA _{out}	LwA	q _V	P _{fs}	q _V	P _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	dB	m ³ /h	Pa	cfm	in. wg
1	3~	400	50	2370	4002	6.28	87	95	98	100	20550	0	12095	0.00
2	3~	400	50	2370	5793	8.93	81	89	92	94	17675	700	10405	2.81
3	3~	400	50	2370	6500	10.00	76	84	89	90	13755	1200	8095	4.82
4	3~	400	50	2370	5991	9.26	80	86	91	92	8365	1600	4925	6.42
5	3~	400	50	1975	2374	4.12	82	91	94	96	17135	0	10085	0.00
6	3~	400	50	1975	3402	5.57	76	84	88	89	14745	485	8675	1.95
7	3~	400	50	1975	3720	6.02	72	79	84	85	11465	842	6750	3.38
8	3~	400	50	1975	3519	5.74	76	82	87	88	6980	1118	4110	4.49
9	3~	400	50	1485	1092	2.40	75	83	86	88	12835	0	7555	0.00
10	3~	400	50	1480	1529	3.01	69	77	80	82	11005	270	6480	1.08
11	3~	400	50	1485	1655	3.18	65	72	77	78	8565	469	5040	1.88
12	3~	400	50	1480	1567	3.06	66	73	79	80	5235	629	3080	2.53
13	3~	400	50	985	401	1.22	66	74	78	79	8560	0	5040	0.00
14	3~	400	50	985	519	1.45	58	67	71	73	7280	118	4285	0.47
15	3~	400	50	985	558	1.52	55	63	68	69	5695	208	3350	0.84
16	3~	400	50	985	534	1.48	56	62	67	68	3485	280	2050	1.12

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
LwA_{out} = Sound power level outlet side · q_V = Air flow · P_{fs} = Pressure increase