

8300101403
VVY0500NSNJS

EC axial panel fan - AxiTone

sickle-shaped blades (S series)

ebm-papst Mulfingen GmbH & Co. KG
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.fansco.com
www.fansco.com

Limited partnership · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRA 590344
General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Item	8300101403	
Motor	E07433-43	
Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 240
Frequency	Hz	50/60
Method of obtaining data		ml
Status		prelim.
Speed (rpm)	min ⁻¹	850
Power consumption	W	153
Current draw	A	1.3
Max. back pressure	Pa	60
Max. back pressure	in. wg	0.24
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · oe = Customer equipment
Subject to change

Data according to Commission Regulation (EU) 327/2011 (prEN 17166)

		Actual	Req. 2015			
01 Overall efficiency η_{es}	%	43.5	28.5	09 Power consumption P_{ed}	kW	0.15
02 Measurement category		A		09 Air flow q_v	m ³ /h	3800
03 Efficiency category		Static		09 Pressure increase p_{fs}	Pa	55
04 Efficiency grade N		55	40	10 Speed (rpm) n	min ⁻¹	850
05 Variable speed drive		Yes		11 Specific ratio*		1.00

Data obtained at optimum efficiency level.
The efficiency values displayed for achieving conformity with the Ecodesign Regulation EU 327/2011 has been reached with defined air duct components (e.g. inlet rings).
The dimensions must be requested from ebm-papst. If other air conduction geometries are used on the installation side, the ebm-papst evaluation loses its validity/the conformity must be confirmed again.
The product does not fall within the scope of Regulation (EU) 2019/1781 due to the exception specified in Article 2 (2a) (motors completely integrated into a product).

* Specific ratio = $1 + p_g / 100\,000\text{ Pa}$ LU-229511

8300101403
VVY0500NSNJS

EC axial panel fan - AxiTone

sickle-shaped blades (S series)

Technical description

Size	500 mm
Motor size	74
Rotor surface	Galvanized
Electronics housing material	Die-cast aluminum
Impeller material	PP plastic
Number of blades	3
Airflow direction	V
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP54
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H1
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Cooling hole/opening	On rotor side
Mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 10 mA - Locked-rotor detection - Tach output - Speed control - Power limiter - Motor current limitation - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Overvoltage detection - Thermal overload protection for electronics/motor - Line undervoltage detection
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC interference emission	According to EN 61000-6-4 (industrial environment)
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Motor protection	Electronic motor protection
With cable	Variable
Protection class assignment	I; If a protective earth is connected. The built-in component has several local protection class assignments. The final protection class is determined by the intended installation.
Conformity with standards	EN 60335-1; EN 60034-1; EN 60204-1; UKCA; CE
Approval	CSA C22.2 No. 77 + CAN/CSA-E60730-1; UL 1004-7 + 60730-1

VVY0500NSNJS

sickle-shaped blades (S series)

The technical drawing illustrates the M6000-10000W fan unit from two perspectives: a side view (left) and a front view (right).

Side View Dimensions:

- Total width: 149 ± 3.1
- Mounting bracket width: 144 ± 3.1
- Internal component width: 133.7 ± 3.1
- Height of the mounting bracket: $\varnothing 132.5$
- Inner diameter of the mounting bracket: $\varnothing 101$
- Outer diameter of the mounting bracket: $\varnothing 75$
- Overall height: $\varnothing 497.8 \pm 1.5$
- Base width: 157 ± 2

Front View Dimensions:

- Number of screws: ③ M4 (5x)
- Number of screws: ② M6 (4x)
- Number of screws: M4 (4x)
- Radius of the outer casing: $R850 \pm 20$
- Radius of the inner casing: $R85 \pm 10$
- Thickness of the inner casing: 6
- Number of blades: ⑤
- Number of wires: ④
- Motor diameter: $\varnothing 58 \pm 0.2$
- Flange diameter: $\varnothing 90 \pm 0.2$
- Outer frame diameter: $\varnothing 125 \pm 0.2$

1	Airflow direction "V"
2	Max. clearance for screw 10 mm
3	Max. clearance for screw 5 mm
4	Supply line (PWR) PVC AWG20
	3x splice
5	Control wire (CTRL) PVC AWG22
	6x splice
6	The diameter of the impeller becomes larger than indicated on the drawing due to the centrifugal forces during operation. The dimension indicated refers to the condition on delivery.

Connection diagram



No.	Conn.	Designation	Color	Function/assignment
	PWR	L	black	Power supply, phase, see nameplate for voltage range
	PWR	N	blue	Power supply, neutral conductor, see nameplate for voltage range
	PWR	PE	green/yellow	Protective earth
	CTRL	GND	blue	Reference ground for control interface, SELV
	CTRL	IO1	yellow	Factory setting: Analog input 0-10 V/PWM, Ri=100 KΩ, fPWM=1 kHz..10 kHz, Function: Speed set value Characteristic curve parameterizable (see "Input curve 1"), SELV Function parameterizable at the factory (see Optional interface functions table)
	CTRL	IO2	white	Factory setting: Open collector output, Umax=50 VDC, Imax= 10 mA, function: Tach output 1 pulse/revolution, SELV Function parameterizable at factory (see table Optional interface functions)
	CTRL	Vout	red	Voltage output 10 VDC +/-3%, Imax=10 mA Short-circuit-proof, power supply for external devices, SELV
	CTRL	-	gray	No function
	CTRL	-	brown	No function


Terminal/plug assignment

		electrical specification		configurable IO mode		INPUT						OUTPUT						signal: configurable function	
IO1																			
IO2																			
Vout																			

Basic (B4)
Factory configuration option upon request

Factory configuration option

Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-229511-1
Date: 2023-10-31
Housing: 10501-2-4037

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _e	I	LpA _{in}	LwA _{in}	LwA _{out}	LwA	q _v	P _{fs}	q _v	P _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	dB	m ³ /h	Pa	cfm	in. wg
1	1~	230	50	900	131	1.11	54	60	59	63	6045	0	3555	0.00
2	1~	230	50	890	147	1.24	51	58	57	60	5365	20	3160	0.08
3	1~	230	50	870	153	1.30	48	54	54	57	4550	40	2675	0.16
4	1~	230	50	850	153	1.30	46	54	53	56	3445	60	2025	0.24
5	1~	230	50	775	84	0.71	50	56	55	59	5210	0	3065	0.00
6	1~	230	50	775	97	0.81	48	54	53	57	4675	15	2750	0.06
7	1~	230	50	775	108	0.91	45	52	52	55	4055	32	2385	0.13
8	1~	230	50	775	118	1.00	44	51	51	54	3165	51	1865	0.20
9	1~	230	50	650	50	0.42	46	52	51	54	4370	0	2570	0.00
10	1~	230	50	650	57	0.48	43	50	49	52	3920	11	2310	0.04
11	1~	230	50	650	64	0.54	40	47	47	50	3400	22	2000	0.09
12	1~	230	50	650	70	0.59	40	47	47	50	2655	36	1560	0.14
13	1~	230	50	525	26	0.22	40	47	45	49	3530	0	2075	0.00
14	1~	230	50	525	30	0.25	38	44	44	47	3165	7	1865	0.03
15	1~	230	50	525	34	0.28	35	42	42	45	2745	15	1615	0.06
16	1~	230	50	525	37	0.31	34	42	41	44	2145	23	1260	0.09

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
LwA_{out} = Sound power level outlet side · q_v = Air flow · P_{fs} = Pressure increase