

**ebm-papst Mulfingen GmbH & Co. KG**

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.fansco.com

www.fansco.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

**Nominal data**

|       |                |  |
|-------|----------------|--|
| Type  | A3G300-AL11-03 |  |
| Motor | M3G055-DF      |  |

|                       |     |            |
|-----------------------|-----|------------|
| Phase                 |     | 1~         |
| Nominal voltage       | VAC | 230        |
| Nominal voltage range | VAC | 200 .. 240 |
| Frequency             | Hz  | 50/60      |


|                          |                   |      |
|--------------------------|-------------------|------|
| Method of obtaining data |                   | ml   |
| Speed (rpm)              | min <sup>-1</sup> | 1560 |
| Power consumption        | W                 | 97   |
| Current draw             | A                 | 0.8  |
| Max. back pressure       | Pa                | 98   |
| Max. back pressure       | in. wg            | 0.39 |
| Min. ambient temperature | °C                | -25  |
| Max. ambient temperature | °C                | 60   |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment  
Subject to change

## Technical description


|                                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|----------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Weight                                                                     | 1.8 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Size                                                                       | 300 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Motor size                                                                 | 55                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Rotor surface                                                              | Passivated                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Impeller material                                                          | PP-GF40 plastic                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Airflow direction                                                          | V                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Direction of rotation                                                      | Counterclockwise, viewed toward rotor                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Degree of protection                                                       | IP54                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Insulation class                                                           | "B"                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Moisture (F) / Environmental (H) protection class                          | H1                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Max. permitted ambient temp. for motor (transport/storage)                 | + 80 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Min. permitted ambient temp. for motor (transport/storage)                 | - 40 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Installation position                                                      | Any                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Condensation drainage holes                                                | None, open rotor                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Mode                                                                       | S1                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Motor bearing                                                              | Ball bearing                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Technical features                                                         | <ul style="list-style-type: none"> <li>- Output 10 VDC, max. 10 mA</li> <li>- Tach output</li> <li>- Power limiter</li> <li>- Motor current limitation</li> <li>- Soft start</li> <li>- Control input 0-10 VDC / PWM</li> <li>- Control interface with SELV potential safely disconnected from the mains</li> <li>- Overvoltage detection</li> <li>- Thermal overload protection for electronics/motor</li> <li>- Line undervoltage detection</li> </ul> |
| EMC immunity to interference                                               | According to EN 61000-6-2 (industrial environment)                                                                                                                                                                                                                                                                                                                                                                                                       |
| EMC circuit feedback                                                       | According to EN 61000-3-2/3                                                                                                                                                                                                                                                                                                                                                                                                                              |
| EMC interference emission                                                  | According to EN 61000-6-3 (household environment)                                                                                                                                                                                                                                                                                                                                                                                                        |
| Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system) | <= 3.5 mA                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Motor protection                                                           | Electronic motor protection                                                                                                                                                                                                                                                                                                                                                                                                                              |
| With cable                                                                 | Variable                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Protection class assignment                                                | <p>I; If a protective earth is connected.</p> <p>The built-in component has several local protection class assignments.</p> <p>The final protection class is determined by the intended installation.</p>                                                                                                                                                                                                                                                |
| Conformity with standards                                                  | EN 60335-1; CE                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Comment on CE                                                              | Ecodesign Directive 2009/125/EC + Fan Directive (EC) No. 327/2011 does not apply, as power consumption <125W.                                                                                                                                                                                                                                                                                                                                            |
| Approval                                                                   | CSA C22.2 No. 77 + CAN/CSA-E60730-1; EAC; UL 1004-7 + 60730-1; CCC                                                                                                                                                                                                                                                                                                                                                                                       |

## Product drawing




|   |                                        |
|---|----------------------------------------|
| 1 | Direction of air flow "V"              |
| 2 | Max. clearance for screw 10 mm         |
| 3 | Max. clearance for screw 5 mm          |
| 4 | Cable PVC 3G AWG20, 3x crimped splices |
| 5 | Cable PVC 4x AWG22, 4x crimped splices |

## Connection diagram



| No. | Conn. | Designation | Color        | Function/assignment                                                                                                                     |
|-----|-------|-------------|--------------|-----------------------------------------------------------------------------------------------------------------------------------------|
|     | CON10 | L           | black        | Supply connection, power supply, phase, see nameplate for voltage range                                                                 |
|     | CON11 | N           | blue         | Supply connection, power supply, neutral conductor, see nameplate for voltage range                                                     |
|     | CON12 | PE          | green/yellow | Ground connection                                                                                                                       |
|     | 2     | 0- 10V PWM  | yellow       | 0-10 V / PWM control input, $R_i=100 \text{ k}\Omega$ , SELV                                                                            |
|     | 4     | Tach        | white        | Tach output, open collector, 1 pulse per revolution, $I_{sink \text{ max}} = 10 \text{ mA}$ , SELV                                      |
|     | 3     | +10 V       | red          | Fixed voltage output 10 VDC $\pm 3 \%$ , $I_{max.} 10 \text{ mA}$ , short-circuit-proof, power supply for ext. devices (e.g. pot), SELV |
|     | 1     | GND         | blue         | Reference ground for control interface, SELV                                                                                            |

## Curves: Air performance 50 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-166935-1  
Date: 2014-10-01  
Housing: 03968-2-4037

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

|    | U   | f  | n                 | P <sub>ed</sub> | I    | LpA <sub>in</sub> | LwA <sub>in</sub> | q <sub>v</sub> | p <sub>fs</sub> | q <sub>v</sub> | p <sub>fs</sub> |
|----|-----|----|-------------------|-----------------|------|-------------------|-------------------|----------------|-----------------|----------------|-----------------|
|    | V   | Hz | min <sup>-1</sup> | W               | A    | dB(A)             | dB(A)             | m³/h           | Pa              | cfm            | in. wg          |
| 1  | 230 | 50 | 1665              | 73              | 0.64 | 58                | 65                | 2250           | 0               | 1325           | 0.00            |
| 2  | 230 | 50 | 1630              | 82              | 0.71 | 58                | 65                | 1850           | 40              | 1090           | 0.16            |
| 3  | 230 | 50 | 1605              | 87              | 0.75 | 58                | 65                | 1505           | 70              | 885            | 0.28            |
| 4  | 230 | 50 | 1560              | 97              | 0.80 | 60                | 68                | 1120           | 98              | 660            | 0.39            |
| 5  | 230 | 50 | 1450              | 48              | 0.42 | 55                | 61                | 1960           | 0               | 1150           | 0.00            |
| 6  | 230 | 50 | 1450              | 58              | 0.50 | 55                | 62                | 1650           | 32              | 970            | 0.13            |
| 7  | 230 | 50 | 1450              | 64              | 0.55 | 56                | 63                | 1360           | 57              | 800            | 0.23            |
| 8  | 230 | 50 | 1450              | 78              | 0.66 | 59                | 66                | 1040           | 85              | 615            | 0.34            |
| 9  | 230 | 50 | 1200              | 27              | 0.24 | 50                | 57                | 1620           | 0               | 955            | 0.00            |
| 10 | 230 | 50 | 1200              | 33              | 0.28 | 50                | 57                | 1365           | 22              | 805            | 0.09            |
| 11 | 230 | 50 | 1200              | 36              | 0.31 | 51                | 58                | 1125           | 39              | 665            | 0.16            |
| 12 | 230 | 50 | 1200              | 44              | 0.38 | 54                | 61                | 860            | 58              | 505            | 0.23            |
| 13 | 230 | 50 | 950               | 14              | 0.12 | 44                | 51                | 1285           | 0               | 755            | 0.00            |
| 14 | 230 | 50 | 950               | 16              | 0.14 | 44                | 51                | 1080           | 14              | 635            | 0.06            |
| 15 | 230 | 50 | 950               | 18              | 0.15 | 45                | 52                | 890            | 25              | 525            | 0.10            |
| 16 | 230 | 50 | 950               | 22              | 0.19 | 48                | 55                | 685            | 36              | 400            | 0.14            |

U = Voltage · f = Frequency · n = Speed (rpm) · P<sub>ed</sub> = Power consumption · I = Current draw · LpA<sub>in</sub> = Sound pressure level intake side · LwA<sub>in</sub> = Sound power level intake side  
q<sub>v</sub> = Air flow · p<sub>fs</sub> = Pressure increase