

K2E220-AB06-09

AC centrifugal fan

forward curved

with housing (without flange)

<https://www.fansco.com>

sales@fansco.com

Nominal data

Type	K2E220-AB06-09		
Motor	M2E068-CF		
Phase		1~	1~
Nominal voltage	VAC	230	230
Frequency	Hz	50	60
Type of data definition		cu	cu
Valid for approval / standard		CE	CE
Speed	min ⁻¹	2550	2700
Power input	W	100	137
Current draw	A	0.45	0.6
Motor capacitor	μF	2.5	2.5
Capacitor voltage	VDB	400	400
Capacitor standard		P0 (CE)	
Min. back pressure	Pa	0	0
Max. ambient temperature	°C	55	55
Starting current	A	0.9	0.92

ml = max. load · me = max. efficiency · fa = running at free air · cs = customer specs · cu = customer unit
Subject to alterations



AC centrifugal fan

forward curved

with housing (without flange)

Technical features


Size	220 mm
Surface of rotor	Coated in black
Material of impeller	Plastic PA6, fibreglass-reinforced
Housing material	Plastic PA6.6, fibreglass-reinforced
Number of blades	11
Direction of rotation	Clockwise, seen on rotor
Type of protection	IP 44; Depending on installation and position as per EN 60034-5
Insulation class	"B"
Humidity class	F1-2
Max. permissible ambient motor temp. (transp./ storage)	+ 80 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Mounting position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensate discharge holes	Rotor-side
Operation mode	S1
Motor bearing	Ball bearing
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	< 0.75 mA
Motor protection	Thermal overload protector (TOP) wired internally
Cable exit	Axial
Product conforming to standard	EN 60335-1; CE
Approval	CCC; UL 2111; CSA C22.2 Nr.77



AC centrifugal fan


forward curved
with housing (without flange)

Product drawing



1	Connection line PVC 3X 0.5mm², 1x Molex connector housing 03-06-2032
1.1	brown
1.2	black
1.3	Blue

Connection screen




U1	Blue	Z	brown	U2	black
----	------	---	-------	----	-------

AC centrifugal fan

forward curved

with housing (without flange)

Charts: Air flow 50 Hz



Measurement: LU-60931

Air performance measured as per ISO 5801
 Installation category A. For detailed
 information on the measuring set-up, please
 contact ebm-papst. Suction-side noise
 levels: L_{WA} measured as per ISO 13347 /
 L_{pA} measured with 1m distance to fan axis.
 The values given are valid under the
 measuring conditions mentioned above and
 may vary according to the actual installation
 situation. With any deviation from the
 standard set-up, the specific values have to
 be checked and reviewed with the unit
 installed.

Measured values

	U	f	n	P _e	I	qv	p _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa
1	230	50	2550	100	0.45	650	0
2	230	50	2515	104	0.46	500	160
3	230	50	2545	100	0.44	355	300
4	230	50	2640	88	0.39	220	400


U = Supply voltage · f = Frequency · n = Speed · P_e = Power input · I = Current draw · qv = Air flow · p_{fs} = Pressure increase



AC centrifugal fan

forward curved
with housing (without flange)

Charts: Air flow 60 Hz



Measurement: LU-60933

Air performance measured as per ISO 5801
Installation category A. For detailed
information on the measuring set-up, please
contact ebm-papst. Suction-side noise
levels: L_{WA} measured as per ISO 13347 /
L_{pA} measured with 1m distance to fan axis.
The values given are valid under the
measuring conditions mentioned above and
may vary according to the actual installation
situation. With any deviation from the
standard set-up, the specific values have to
be checked and reviewed with the unit
installed.

Measured values

	U	f	n	P _e	I	qv	p _{fs}
	V	Hz	min ⁻¹	W	A	m³/h	Pa
1	230	60	2700	137	0.60	700	0
2	230	60	2650	140	0.61	550	150
3	230	60	2675	138	0.60	410	300
4	230	60	2860	126	0.55	280	450

U = Supply voltage · f = Frequency · n = Speed · P_e = Power input · I = Current draw · qv = Air flow · p_{fs} = Pressure increase

