

# EC centrifugal module - RadiCal

backward-curved, single-intake

with support bracket

**ebm-papst Mulfingen GmbH & Co. KG**

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.fansco.com

www.fansco.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

## Nominal data

|                          |                   |            |
|--------------------------|-------------------|------------|
| Type                     | K3G560-RA25-21    |            |
| Motor                    | M3G150-FF         |            |
| Phase                    |                   | 1~         |
| Nominal voltage          | VAC               | 230        |
| Nominal voltage range    | VAC               | 200 .. 277 |
| Frequency                | Hz                | 50/60      |
| Method of obtaining data |                   | ml         |
| Speed (rpm)              | min <sup>-1</sup> | 1340       |
| Power consumption        | W                 | 1500       |
| Current draw             | A                 | 6.7        |
| Min. ambient temperature | °C                | -25        |
| Max. ambient temperature | °C                | 50         |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment

Subject to change

## Data according to Commission Regulation (EU) 327/2011 (prEN 17166)

|                                   |   | Actual | Req. 2015 |                               |                   |      |
|-----------------------------------|---|--------|-----------|-------------------------------|-------------------|------|
| 01 Overall efficiency $\eta_{es}$ | % | 63.5   | 53.4      | 09 Power consumption $P_{ed}$ | kW                | 1.5  |
| 02 Measurement category           |   | A      |           | 09 Air flow $q_v$             | m <sup>3</sup> /h | 7240 |
| 03 Efficiency category            |   | Static |           | 09 Pressure increase $p_{fs}$ | Pa                | 444  |
| 04 Efficiency grade N             |   | 72.1   | 62        | 10 Speed (rpm) n              | min <sup>-1</sup> | 1300 |
| 05 Variable speed drive           |   | Yes    |           | 11 Specific ratio*            |                   | 1.00 |

Data obtained at optimum efficiency level.

\* Specific ratio =  $1 + p_b / 100\,000\text{ Pa}$ 

LU-179863

The efficiency values displayed for achieving conformity with the Ecodesign Regulation EU 327/2011 has been reached with defined air duct components (e.g. inlet rings). The dimensions must be requested from ebm-papst. If other air conduction geometries are used on the installation side, the ebm-papst evaluation loses its validity/the conformity must be confirmed again. The product does not fall within the scope of Regulation (EU) 2019/1781 due to the exception specified in Article 2 (2a) (motors completely integrated into a product).

## Technical description

|                                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|----------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Weight                                                                     | 44.6 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Size                                                                       | 560 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Motor size                                                                 | 150                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Rotor surface                                                              | Painted black                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Electronics housing material                                               | Die-cast aluminum                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Impeller material                                                          | PP plastic                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Support plate material                                                     | Sheet steel, galvanized                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Support bracket material                                                   | Steel, painted black                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Inlet nozzle material                                                      | Sheet steel, galvanized                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Number of blades                                                           | 6                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Direction of rotation                                                      | Clockwise, viewed toward rotor                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Degree of protection                                                       | IP55                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Insulation class                                                           | "F"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Moisture (F) / Environmental (H) protection class                          | H1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Max. permitted ambient temp. for motor (transport/storage)                 | +80 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Min. permitted ambient temp. for motor (transport/storage)                 | -40 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Installation position                                                      | See legend on product drawing                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Condensation drainage holes                                                | On rotor side                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Mode                                                                       | S1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Motor bearing                                                              | Ball bearing                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Technical features                                                         | <ul style="list-style-type: none"> <li>- Output 10 VDC, max. 10 mA</li> <li>- Output 20 VDC, max. 50 mA</li> <li>- Output for slave 0-10 V</li> <li>- Tach output</li> <li>- Input for sensor 0-10 V or 4-20 mA</li> <li>- External 24 V input (parameter setting)</li> <li>- External release input</li> <li>- Alarm relay</li> <li>- Integrated PID controller</li> <li>- Power limiter</li> <li>- Motor current limitation</li> <li>- PFC, active</li> <li>- RS-485 MODBUS-RTU</li> <li>- Soft start</li> <li>- Control input 0-10 VDC / PWM</li> <li>- Control interface with SELV potential safely disconnected from the mains</li> <li>- Thermal overload protection for electronics/motor</li> <li>- Line undervoltage / phase failure detection</li> </ul> |
| Power Factor Correction (PFC)                                              | Active                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system) | <= 3.5 mA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Electrical hookup                                                          | Terminal box                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Motor protection                                                           | Reverse polarity and locked-rotor protection                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

# EC centrifugal module - RadiCal

backward-curved, single-intake  
with support bracket


|                             |                                                                                                                                                                                            |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protection class assignment | I; If a protective earth is connected.<br>The built-in component has several local protection class assignments.<br>The final protection class is determined by the intended installation. |
| Conformity with standards   | EN 61800-5-1; CE                                                                                                                                                                           |
| Approval                    | UL 1004-7 + 60730-1; EAC; CSA C22.2 No. 77 + CAN/CSA-E60730-1                                                                                                                              |

# EC centrifugal module - RadiCal

backward-curved, single-intake


with support bracket

## Product drawing



|   |                                                                                                                                          |
|---|------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | Installed position: shaft horizontal (install support struts only vertically as illustrated) or rotor on bottom; rotor on top on request |
| 2 | Cable diameter min. 4 mm, max. 10 mm, tightening torque $4 \pm 0.6$ Nm                                                                   |
| 3 | Tightening torque $3.5 \pm 0.5$ Nm                                                                                                       |

## Connection diagram



| No. | Conn. | Designation | Function/assignment                                                                                                             |
|-----|-------|-------------|---------------------------------------------------------------------------------------------------------------------------------|
| KL1 | 1     | L1          | Supply connection, power supply; for nominal voltage range see technical data                                                   |
| KL1 | 2     | N           | Supply connection, power supply; for nominal voltage range see technical data                                                   |
| PE  |       | PE          | Ground connection, PE connection                                                                                                |
| KL2 | 1     | NO          | Status relay, floating status contact, make for failure                                                                         |
| KL2 | 2     | COM         | Status relay, floating status contact, changeover contact, common connection, contact rating 250 VAC/ max. 2 A (AC1)/min. 10 mA |
| KL2 | 3     | NC          | Status relay, floating status contact, break for failure                                                                        |
| KL3 | 1     | RSA         | Bus connection RS485, RSA, MODBUS-RTU; SELV                                                                                     |
| KL3 | 2     | RSB         | Bus connection RS485, RSB, MODBUS-RTU; SELV                                                                                     |
| KL3 | 3     | GND         | Reference ground for control interface; SELV                                                                                    |
| KL3 | 4     | Ain1 U      | Analog input 1, set value: 0-10 V, Ri = 100 kΩ, adjustable curve, only usable as alternative to input Ain1 I; SELV              |


# EC centrifugal module - RadiCal

backward-curved, single-intake

with support bracket

| No. | Conn. | Designation | Function/assignment                                                                                                                                                                                                                                                                        |
|-----|-------|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| KL3 | 5     | + 10 V      | Fixed voltage output 10 VDC, + 10 V +/-3%, max. 10 mA, short-circuit-proof, power supply for ext. devices (e.g. potentiometers); SELV                                                                                                                                                      |
| KL3 | 6     | Ain1 I      | Analog input 1, set value: 4-20 mA, Ri = 100 Ω, adjustable curve, only usable as alternative to input Ain1 U; SELV                                                                                                                                                                         |
| KL3 | 7     | Din1        | Digital input 1: enable electronics,<br>enable: pin open or applied voltage 5-50 VDC<br>disable: bridge to GND or applied voltage < 1 VDC<br>reset function: triggers software reset after a level change to < 1 VDC; SELV                                                                 |
| KL3 | 8     | Din2        | Digital input 2: Switching parameter sets 1/2, according to EEPROM setting, the valid or used parameter set can be selected via bus or via digital input DIN2.<br>Parameter set 1: pin open or applied voltage 5-50 VDC<br>Parameter set 2: bridge to GND or applied voltage < 1 VDC; SELV |
| KL3 | 9     | Din3        | Digital input 3: according to EEPROM setting, the integrated controller's direction of action can be selected via bus or digital input Din3;<br>normal: pin open or applied voltage 5-50 VDC<br>inverse: bridge to GND or applied voltage < 1 VDC; SELV                                    |
| KL3 | 10    | GND         | Reference ground for control interface, SELV                                                                                                                                                                                                                                               |
| KL3 | 11    | Ain2 U      | Analog input 2, measured value: 0-10 V, Ri = 100 kΩ, adjustable curve, only usable as alternative to input Ain2 I; SELV                                                                                                                                                                    |
| KL3 | 12    | + 20 V      | Fixed voltage output 20 VDC, + 20 V +25/-10%, max. 50 mA, short-circuit-proof, power supply for ext. devices (e.g. sensors); SELV<br>Alternatively: +24 VDC input for parameterization without line voltage                                                                                |
| KL3 | 13    | Ain2 I      | Analog input 2, measured value: 4-20 mA, Ri = 100 Ω, adjustable curve, only usable as alternative to input Ain2 U; SELV                                                                                                                                                                    |
| KL3 | 14    | Aout        | Analog output 0-10 VDC, max. 5 mA, output of current motor modulation level / motor speed adjustable curve; SELV                                                                                                                                                                           |

## Curves: Air performance 50 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-179863-1

Date: 2016-06-09

Nozzle: 54482-2-4013

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

|    | U   | f  | n                 | P <sub>ed</sub> | I    | LpA <sub>in</sub> | LwA <sub>in</sub> | LwA <sub>out</sub> | q <sub>v</sub> | P <sub>fs</sub> | q <sub>v</sub> | P <sub>fs</sub> |
|----|-----|----|-------------------|-----------------|------|-------------------|-------------------|--------------------|----------------|-----------------|----------------|-----------------|
|    | V   | Hz | min <sup>-1</sup> | W               | A    | dB(A)             | dB(A)             | dB(A)              | m³/h           | Pa              | cfm            | in. wg          |
| 1  | 230 | 50 | 1340              | 1145            | 5.03 | 75                | 83                | 86                 | 11620          | 0               | 6840           | 0.00            |
| 2  | 230 | 50 | 1340              | 1469            | 6.46 | 71                | 79                | 83                 | 9805           | 250             | 5770           | 1.00            |
| 3  | 230 | 50 | 1340              | 1500            | 6.70 | 66                | 74                | 79                 | 7095           | 450             | 4175           | 1.81            |
| 4  | 230 | 50 | 1340              | 1480            | 6.47 | 69                | 77                | 81                 | 5020           | 580             | 2955           | 2.33            |
| 5  | 230 | 50 | 1200              | 813             | 3.57 | 73                | 80                | 83                 | 10365          | 0               | 6100           | 0.00            |
| 6  | 230 | 50 | 1200              | 1052            | 4.63 | 68                | 76                | 80                 | 8790           | 203             | 5175           | 0.81            |
| 7  | 230 | 50 | 1200              | 1184            | 5.20 | 64                | 72                | 77                 | 6540           | 385             | 3850           | 1.55            |
| 8  | 230 | 50 | 1200              | 1076            | 4.67 | 66                | 74                | 79                 | 4510           | 470             | 2655           | 1.89            |
| 9  | 230 | 50 | 1000              | 471             | 2.07 | 68                | 76                | 79                 | 8640           | 0               | 5085           | 0.00            |
| 10 | 230 | 50 | 1000              | 609             | 2.68 | 63                | 71                | 75                 | 7325           | 141             | 4310           | 0.57            |
| 11 | 230 | 50 | 1000              | 685             | 3.01 | 60                | 68                | 72                 | 5450           | 268             | 3205           | 1.08            |
| 12 | 230 | 50 | 1000              | 622             | 2.70 | 61                | 69                | 74                 | 3755           | 326             | 2210           | 1.31            |
| 13 | 230 | 50 | 800               | 241             | 1.06 | 62                | 70                | 73                 | 6910           | 0               | 4070           | 0.00            |
| 14 | 230 | 50 | 800               | 312             | 1.37 | 58                | 66                | 70                 | 5860           | 90              | 3450           | 0.36            |
| 15 | 230 | 50 | 800               | 351             | 1.54 | 54                | 62                | 66                 | 4360           | 171             | 2565           | 0.69            |
| 16 | 230 | 50 | 800               | 319             | 1.38 | 56                | 64                | 69                 | 3005           | 209             | 1770           | 0.84            |

U = Voltage · f = Frequency · n = Speed (rpm) · P<sub>ed</sub> = Power consumption · I = Current draw · LpA<sub>in</sub> = Sound pressure level intake side · LwA<sub>in</sub> = Sound power level intake side  
 LwA<sub>out</sub> = Sound power level outlet side · q<sub>v</sub> = Air flow · P<sub>fs</sub> = Pressure increase