

www.fansco.com
sales@fansco.com

Nominal data

Type	M4Q045-CA01-75		
Motor	M4Q045-CA		
Phase		1~	1~
Nominal voltage	VAC	230	230
Frequency	Hz	50	60
Type of data definition		me	me
Valid for approval / standard		CE	CE
Speed	min ⁻¹	1300	1550
Power input	W	31	30
Power output	W	7	8
Current draw	A	0.2	0.2
Max. ambient temperature	°C	-	-


ml = max. load · me = max. efficiency · fa = running at free air · cs = customer specs · cu = customer unit
Subject to alterations



Technical features


Mass	1.1 kg
Size	45 mm
Material of end shield	Die-cast aluminium
Direction of rotation	Counter-clockwise, seen on rotor
Type of protection	IP 20
Insulation class	"B"
Max. permissible ambient motor temp. (transp./ storage)	+ 80 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Mounting position	Shaft horizontal
Condensate discharge holes	None
Operation mode	S1
Motor bearing	Calotte bearing
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	< 0.75 mA
Motor protection	Impedance protected
Cable exit	Lateral
Protection class	I (if protective earth is connected by customer)
Product conforming to standard	EN 60335-1; CE
Approval	VDE

Product drawing



- | | |
|---|--|
| 1 | Connection line PVC, 3x brass lead tips crimped |
| 2 | Nut tightening torque, for fastening the wall ring or guard grille: 2.3 Nm |
| 3 | Screw tightening torque, for fastening the impeller: 1.4 Nm |
| 4 | Nut tightening torque, for fastening the mounting bracket: 2.3 Nm |
| 5 | Direction of rotation counter-clockwise, seen on shaft end |

Connection screen



L	blue	PE	green/yellow	N	brown
---	------	----	--------------	---	-------

Charts: Speed

