

EC centrifugal fan - RadiPac

backward-curved, single-intake

ebm-papst Mulfingen GmbH & Co. KG

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.fansco.com

www.fansco.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Type	R3G500-PB24-02	
Motor	M3G150-IF	
Phase		3~
Nominal voltage	VAC	400
Nominal voltage range	VAC	380 .. 480
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min ⁻¹	2000
Power consumption	W	3900
Current draw	A	6.0
Min. ambient temperature	°C	-40
Max. ambient temperature	°C	45

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment

Subject to change

Data according to Commission Regulation (EU) 327/2011 (prEN 17166)

		Actual	Req. 2015			
01 Overall efficiency η_{es}	%	70.8	57.6	09 Power consumption P_{ed}	kW	3.84
02 Measurement category		A		09 Air flow q_v	m ³ /h	8700
03 Efficiency category		Static		09 Pressure increase p_{fs}	Pa	1082
04 Efficiency grade N		75.2	62	10 Speed (rpm) n	min ⁻¹	1995
05 Variable speed drive		Yes		11 Specific ratio*		1.01

Data obtained at optimum efficiency level.

* Specific ratio = $1 + p_b / 100\,000\text{ Pa}$


LU-205682

The efficiency values displayed for achieving conformity with the Ecodesign Regulation EU 327/2011 has been reached with defined air duct components (e.g. inlet rings). The dimensions must be requested from ebm-papst. If other air conduction geometries are used on the installation side, the ebm-papst evaluation loses its validity/the conformity must be confirmed again. The product does not fall within the scope of Regulation (EU) 2019/1781 due to the exception specified in Article 2 (2a) (motors completely integrated into a product).

Technical description

Weight	24.8 kg
Size	500 mm
Motor size	150
Rotor surface	Painted black
Electronics housing material	Die-cast aluminum
Impeller material	Sheet aluminum
Number of blades	5
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP55
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	H1
Ambient temperature note	Occasional start-up at temperatures between -40°C and -25°C is permitted. For continuous operation at ambient temperatures below -25°C (such as refrigeration applications), use must be made of a fan design with special low-temperature bearings.
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing
Technical features	- Operation and alarm display with LED - External 15-50 VDC input (parameterization) - Alarm relay - Integrated PI controller - Configurable inputs/outputs (I/O) - MODBUS V6.3 - Motor current limitation - RS-485 MODBUS-RTU - Soft start - Voltage output 3.3-24 VDC, Pmax = 800 mW - Control interface with SELV potential safely disconnected from the mains - Thermal overload protection for electronics/motor - Line undervoltage / phase failure detection
Power Factor Correction (PFC)	Passive (through low-capacitance DC link)
EMC immunity to interference	According to EN 61000-6-2 (industrial environment)
EMC interference emission	According to EN 61000-6-3 (household environment), except EN 61000-3-2 for professionally used equipment with a total rated power greater than 1 kW
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Electrical hookup	Terminal box
Motor protection	Reverse polarity and locked-rotor protection
Protection class assignment	I; If a protective earth is connected. The built-in component has several local protection class assignments. The final protection class is determined by the intended installation.
Conformity with standards	EN 61800-5-1; CE


Product drawing



(The tightening torque is designed for PVC cables. If the cable materials are different, the tightening torque may have to be adjusted)


4	Tightening torque 1.5 ± 0.2 Nm
1	Accessory part: Inlet ring 64025-2-4013 with pressure tap (k-factor: 281) not included in scope of delivery
2	Max. clearance for screw 20 mm
3	Cable diameter min. 4 mm, max. 10 mm, tightening torque 4 ± 0.6 Nm

Accessory part



Inlet ring 64025-2-4013 with pressure tap (k-factor: 281)

Connection diagram




No.	Conn.	Designation	Function/assignment
	CON1	L1, L2, L3	Power supply, phase, see nameplate for voltage range
	PE	PE	Protective earth
	CON2	RSA	RS485 interface for MODBUS, RSA; SELV
	CON2	RSB	RS485 interface for MODBUS, RSB; SELV
	CON2	GND	Reference ground for control interface, SELV
	CON2	IO1	Function parameterizable (see "Optional interface functions" table) Factory setting: Digital input - high active, function: Disable input, SELV - inactive: Pin open or applied voltage < 1.5 VDC - active: applied voltage 3.5-50 VDC Reset function: Triggering of error reset on change of state from "enabled" to "disabled"
	CON2	IO2	Function parameterizable (see "Optional interface functions" table) Factory setting: Analog input 0-10 V / PWM, R _i =100 kΩ, function: Set value Characteristic curve parameterizable (see input characteristic curve P1-IN), SELV
	CON2	IO3	Function parameterizable (see "Optional interface functions" table) Factory setting: Analog output 0-10 V, max. 5 mA, function: Fan modulation level Characteristic curve parameterizable (see output characteristic curve P3-OUT), SELV
	CON2	Vout	Voltage output 3.3-24 VDC ±5%, P _{max} =800 mW, voltage parameterizable Factory setting: 10 VDC short-circuit-proof, supply for external devices, SELV alternatively: 15-50 VDC input for parameterization via MODBUS without line voltage
	CON2	COM	Status relay, floating status contact, common connection, contact rating 250 VAC / 2 A (AC1) / min. 10 mA, reinforced insulation on supply side and on control interface side
	CON2	NC	Status relay, floating status contact, break for failure
		LED	green: status = good, ready for operation orange: status = warning red: status = failure
		P1-IN	Input characteristic curve
		P3-OUT	Output characteristic curve

Terminal/plug assignment

configurable option		For further information and additional functions see EC Control Software, Fan-Set-App, or MODBUS Parameter Specification V6.3		configurable IO functions: normal / inverse	MODBUS Register for IO mode configuration	electrical specification	configurable IO mode	CON2	OUTPUT																	
									INPUT																	
IO1	○ Din1 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D158 [0]	○	○	switch: fan enable / disable	(selected directly via IO mode)	D130 [10]	signal: fan modulation level %	D130 [11]	signal: actual speed	D130 [12]	signal: system modulation level %	D130 [5]	signal: remote control output 0-10V	D130 [4]	pulse input for auto-addressing	D130 [1]	pulse output for auto-addressing							
	○ Ain1 0-10V/PWM: analog input	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	D158 [2]	○	○	switch: control function: heating (pos.) / cooling (neg.)	(selected directly via IO mode)	D148 [...]	switch: direction of rotation: cw / ccw	D16C [...]	D16A [...]															
	○ Tach out (open collector output)	Umax = 50VDC, Imax = 20mA, SELV	D158 [5]	○	○	switch: parameter set: #1 / #2		D104 [...]	source: sensor value	D147 [...]	D12E [...]															
	○ Diagnostics out (open collector output)	Umax = 50VDC, Imax = 20mA, SELV	D158 [6]																							
IO2	○ Din2 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D159 [0]	○	○	switch: control function: heating (pos.) / cooling (neg.)	(selected directly via IO mode)	D148 [...]	switch: direction of rotation: cw / ccw	D16C [...]	D16A [...]															
	○ Ain2 0-10V/PWM: analog input	RI = 100K, characteristic curve parameterizable, f _{PWM} = 1k..10KHz, SELV	D159 [2]	○	○	switch: parameter set: #1 / #2		D104 [...]	source: sensor value	D147 [...]	D12E [...]															
	○ Ain2 4-20mA: analog input	RI = 125R, characteristic curve parameterizable, SELV	D159 [3]																							
	○ Din3 (active high): digital input	active: applied voltage 3.5-50VDC, SELV not active: pin open or applied voltage < 1.5VDC	D15A [0]	○	○	switch: fan enable / disable	(selected directly via IO mode)	D130 [10]	signal: fan modulation level %	D130 [11]	signal: actual speed	D130 [12]	signal: system modulation level %	D130 [5]	signal: remote control output 0-10V	D130 [4]	pulse input for auto-addressing	D130 [1]	pulse output for auto-addressing							
IO3	○ Din3 (active low): digital input	active: applied voltage < 1.5VDC, SELV not active: pin open or applied voltage 3.5-50VDC	D15A [1]	○	○	switch: control function: heating (pos.) / cooling (neg.)	(selected directly via IO mode)	D148 [...]	switch: direction of rotation: cw / ccw	D16C [...]	D16A [...]															
	○ PWMIn3: digital input, idle level high	PWM = 40Hz - 10KHz, characteristics parameterizable active: pin open or applied voltage 3.5-50VDC not active: applied voltage < 1.5VDC, SELV	D15A [7]	○	○	switch: parameter set: #1 / #2		D104 [...]	source: sensor value	D147 [...]	D12E [...]															
	○ PWMIn3: digital input, idle level low	40Hz - 10KHz, characteristics parameterizable active: applied voltage 3.5-50VDC not active: pin open or applied voltage < 1.5VDC, SELV	D15A [8]	○	○	switch: control function: heating (pos.) / cooling (neg.)	(selected directly via IO mode)	D148 [...]	switch: direction of rotation: cw / ccw	D16C [...]	D16A [...]															
	○ Aout3 0-10V: analog output	function parameterizable, max. 5mA max output frequency 300Hz, SELV	D15A [4]																							
RSA RSB	○ Tacho out (pulses), analog output	0-10V max. 5mA max output frequency 300Hz, SELV	D15A [5]			switch: parameter set: #1 / #2		D104 [...]	source: sensor value	D147 [...]	D12E [...]															
	○ Diagnostics out (pulses)	0-10V max. 5mA max output frequency 300Hz, SELV	D15A [6]																							
	○ RS485 bus connection,	MODBUS RTU, specification V6.3, SELV		○	○	switch: fan enable / disable	(selected directly via IO mode)	D130 [10]	signal: fan modulation level %	D130 [11]	signal: actual speed	D130 [12]	signal: system modulation level %	D130 [5]	signal: remote control output 0-10V	D130 [4]	pulse input for auto-addressing	D130 [1]	pulse output for auto-addressing							
	○ voltage output	voltage parameterizable 3.3..24VDC +/- 5%, Pmax=800mW, short-circuit-proof, supply for external devices, SELV	D16E [...]	○	○	switch: control function: heating (pos.) / cooling (neg.)	(selected directly via IO mode)	D148 [...]	switch: direction of rotation: cw / ccw	D16C [...]	D16A [...]															
Vout	alternatively: Input auxiliary power supply for parameterization via RS485/MODBUS RTU without line voltage	15...50VDC																								

Curves: Air performance 50 Hz



$$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$$

Measurement: LU-205682-1
Date: 2020-03-19
Nozzle: 63072-2-4013

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Wired	U	f	n	P _{ed}	I	LpA _{in}	LwA _{in}	LwA _{out}	q _v	p _{fs}	q _v	p _{fs}
		V	Hz	min ⁻¹	W	A	dB(A)	dB(A)	dB(A)	m ³ /h	Pa	cfm	in. wg
1	3~	400	50	2000	2289	3.55	96	103	101	15990	0	9410	0.00
2	3~	400	50	2000	3292	5.03	87	94	95	13115	500	7720	2.01
3	3~	400	50	2000	3900	6.00	79	86	89	9445	1000	5560	4.01
4	3~	400	50	2000	3725	5.68	83	89	92	5990	1300	3525	5.22
5	3~	400	50	1810	1731	2.73	91	99	99	14505	0	8540	0.00
6	3~	400	50	1775	2325	3.61	84	91	92	11600	392	6830	1.57
7	3~	400	50	1745	2602	4.02	76	82	86	8250	764	4855	3.07
8	3~	400	50	1760	2563	3.96	78	85	89	5285	1013	3110	4.07
9	3~	400	50	1605	1235	2.02	90	96	96	12795	0	7530	0.00
10	3~	400	50	1555	1573	2.51	81	88	90	10130	299	5965	1.20
11	3~	400	50	1550	1832	2.88	73	80	83	7320	602	4305	2.42
12	3~	400	50	1560	1787	2.82	74	81	86	4675	793	2750	3.18
13	3~	400	50	1345	764	1.37	84	91	92	10590	0	6230	0.00
14	3~	400	50	1320	1018	1.72	76	83	85	8630	217	5080	0.87
15	3~	400	50	1315	1159	1.91	69	76	80	6215	434	3660	1.74
16	3~	400	50	1320	1133	1.88	70	77	82	3960	569	2330	2.28

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
LwA_{out} = Sound power level outlet side · q_v = Air flow · p_{fs} = Pressure increase