

with inlet ring and guard grill

**ebm-papst Mulfingen GmbH & Co. KG**

Bachmühle 2 · D-74673 Mulfingen

Phone +49 7938 81-0

Fax +49 7938 81-110

info1@de.fansco.com

www.fansco.com

Limited partnership · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen

Amtsgericht (court of registration) Stuttgart · HRB 590142

**Nominal data**

|                             |                   |         |
|-----------------------------|-------------------|---------|
| Type                        | W4E500-XL07-01    |         |
| Motor                       | M4E110-GF         |         |
| Phase                       |                   | 1~      |
| Nominal voltage             | VAC               | 230     |
| Frequency                   | Hz                | 50      |
| Method of obtaining data    |                   | ml      |
| Valid for approval/standard |                   | CE      |
| Speed (rpm)                 | min <sup>-1</sup> | 1300    |
| Power consumption           | W                 | 815     |
| Current draw                | A                 | 3.7     |
| Capacitor                   | µF                | 14      |
| Capacitor voltage           | VDB               | 400     |
| Capacitor standard          |                   | S0 (CE) |
| Max. back pressure          | Pa                | 180     |
| Max. back pressure          | in. wg            | 0.72    |
| Min. ambient temperature    | °C                | -40     |
| Max. ambient temperature    | °C                | 60      |
| Starting current            | A                 | 9.0     |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment  
Subject to change

**Data according to Commission Regulation (EU) 327/2011 (EN 17166)**

|                                   |   | Actual | Req. 2015 |                               |                   |      |
|-----------------------------------|---|--------|-----------|-------------------------------|-------------------|------|
| 01 Overall efficiency $\eta_{es}$ | % | 38.8   | 33.1      | 09 Power consumption $P_e$    | kW                | 0.79 |
| 02 Measurement category           |   | A      |           | 09 Air flow $q_v$             | m <sup>3</sup> /h | 6355 |
| 03 Efficiency category            |   | Static |           | 09 Pressure increase $p_{fs}$ | Pa                | 176  |
| 04 Efficiency grade N             |   | 45.7   | 40        | 10 Speed (rpm) n              | min <sup>-1</sup> | 1325 |
| 05 Variable speed drive           |   | No     |           | 11 Specific ratio*            |                   | 1.00 |

Data obtained at optimum efficiency level.

The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

\* Specific ratio =  $1 + p_g / 100\,000\text{ Pa}$ 

LU-205089




## Technical description

|                                                                            |                                                                                                                                                                                                                                                      |
|----------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Size                                                                       | 500 mm                                                                                                                                                                                                                                               |
| Motor size                                                                 | 110                                                                                                                                                                                                                                                  |
| Rotor surface                                                              | Cast in aluminum, painted black                                                                                                                                                                                                                      |
| Terminal box material                                                      | PP plastic                                                                                                                                                                                                                                           |
| Impeller material                                                          | PP plastic, galvanized sheet-metal plate                                                                                                                                                                                                             |
| Inlet ring material                                                        | Sheet steel, galvanized and coated with black plastic (RAL 9005)                                                                                                                                                                                     |
| Guard grille material                                                      | Steel, coated with black plastic (RAL 9005)                                                                                                                                                                                                          |
| Number of blades                                                           | 5                                                                                                                                                                                                                                                    |
| Airflow direction                                                          | V                                                                                                                                                                                                                                                    |
| Direction of rotation                                                      | Clockwise, viewed toward rotor                                                                                                                                                                                                                       |
| Degree of protection                                                       | IP54                                                                                                                                                                                                                                                 |
| Insulation class                                                           | "F"                                                                                                                                                                                                                                                  |
| Moisture (F) / Environmental (H) protection class                          | H2                                                                                                                                                                                                                                                   |
| Ambient temperature note                                                   | Occasional start-up at temperatures between -40°C and -25°C is permitted. For continuous operation at ambient temperatures below -25°C (such as refrigeration applications), use must be made of a fan design with special low-temperature bearings. |
| Max. permitted ambient temp. for motor (transport/storage)                 | +80 °C                                                                                                                                                                                                                                               |
| Min. permitted ambient temp. for motor (transport/storage)                 | -40 °C                                                                                                                                                                                                                                               |
| Installation position                                                      | Shaft horizontal or rotor on bottom; rotor on top on request                                                                                                                                                                                         |
| Condensation drainage holes                                                | On rotor side                                                                                                                                                                                                                                        |
| Mode                                                                       | S1                                                                                                                                                                                                                                                   |
| Motor bearing                                                              | Ball bearing                                                                                                                                                                                                                                         |
| Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system) | <= 3.5 mA                                                                                                                                                                                                                                            |
| Electrical hookup                                                          | Terminal box                                                                                                                                                                                                                                         |
| Motor protection                                                           | Thermal overload protector (TOP) with basic insulation                                                                                                                                                                                               |
| With cable                                                                 | Axial                                                                                                                                                                                                                                                |
| Protection class                                                           | I (with customer connection of protective earth)                                                                                                                                                                                                     |
| Motor capacitor according to EN 60252-1 in safety protection class         | S0                                                                                                                                                                                                                                                   |
| Conformity with standards                                                  | EN 60034-1 (2010); CE                                                                                                                                                                                                                                |
| Approval                                                                   | EAC; VDE                                                                                                                                                                                                                                             |




## Product drawing



|   |                                                                        |
|---|------------------------------------------------------------------------|
| 1 | Airflow direction "V"                                                  |
| 2 | Tightening torque $1.5 \pm 0.2$ Nm                                     |
| 3 | Cable diameter min. 6 mm, max. 12 mm, tightening torque $2 \pm 0.3$ Nm |

with inlet ring and guard grill


## Connection diagram



|    |              |     |       |   |              |
|----|--------------|-----|-------|---|--------------|
| L  | = U1 = blue  | Z   | brown | N | = U2 = black |
| PE | green/yellow | TOP | gray  |   |              |



Curves: Air performance 50 Hz



$\rho = 1.15 \text{ kg/m}^3 \pm 2 \%$

Measurement: LU-205083-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

|   | Wired | U   | f  | n                 | P <sub>e</sub> | I    | q <sub>v</sub>    | p <sub>fs</sub> | q <sub>v</sub> | p <sub>fs</sub> |
|---|-------|-----|----|-------------------|----------------|------|-------------------|-----------------|----------------|-----------------|
|   |       | V   | Hz | min <sup>-1</sup> | W              | A    | m <sup>3</sup> /h | Pa              | cfm            | in. wg          |
| 1 | 1~    | 230 | 50 | 1375              | 647            | 2.90 | 9390              | 0               | 5525           | 0.00            |
| 2 | 1~    | 230 | 50 | 1355              | 711            | 3.18 | 8410              | 60              | 4950           | 0.24            |
| 3 | 1~    | 230 | 50 | 1335              | 774            | 3.46 | 7220              | 120             | 4250           | 0.48            |
| 4 | 1~    | 230 | 50 | 1300              | 815            | 3.70 | 5485              | 180             | 3230           | 0.72            |

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P<sub>e</sub> = Power consumption · I = Current draw · q<sub>v</sub> = Air flow · p<sub>fs</sub> = Pressure increase

